

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area CS-46 [PM6-3452931] KAESER 4101700 - JENSEN

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06196767	UCH06061287	
Sample Date		Client Info		22 May 2024	28 Dec 2023	
Machine Age	hrs	Client Info		26525	11864	
Oil Age	hrs	Client Info		2733	0	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>10	<1	<1	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	<1	<1	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	2	2	
Lead	ppm	ASTM D5185m	>10	<1	0	
Copper	ppm	ASTM D5185m	>50	<1	6	
Tin	ppm	ASTM D5185m	>10	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1.5	0	0	
Barium	ppm	ASTM D5185m	0	14	0	
Molybdenum	ppm	ASTM D5185m	0	<1	0	
Manganese	ppm	ASTM D5185m	0.3	0	0	
Magnesium	ppm	ASTM D5185m	0	<1	0	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	406	132	263	
Zinc	ppm	ASTM D5185m	0	0	0	
Sulfur	ppm	ASTM D5185m	1283	1024	3232	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	5	
Sodium	ppm	ASTM D5185m		0	0	
Potassium	ppm	ASTM D5185m	>20	<1	1	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	0.17	0.25	



OIL ANALYSIS REPORT

VISUAL



	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
May22/24	Odor	scalar	*Visual	NORML	NORML	NORML	
2	Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
	Free Water		*Visual	>0.05	NEG	NEG	
		scalar	VISUAI		NEG	NEG	
	FLUID PROPER	RTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	47.9	47.9	47.4	
	SAMPLE IMAGI	ES	method	limit/base	current	history1	history2
May2224	Color						no image
	Bottom						no image
	E 6 4 2 4						
	Non-ferrous Met			May22/24			
	Non-ferrous Met			Ma/22/24	Acid Number		
	Non-ferrous Met			0.00 H0 0.40	Base		
	Non-ferrous Met			0.00 H0 0.40	Base		
	Non-ferrous Met			0.00 H0 0.40	Base		
	Non-ferrous Met			0.00 H0 0.40	Base		
	Non-ferrous Met			May22024 002.0 002.0 01.0 00.0 00.0 0 00.0	Base		
	Non-ferrous Met			May22024 002.0 002.0 01.0 00.0 00.0 0 00.0	Base		
	Non-ferrous Met			0.00 H0 0.40	Base		

Report Id: UCCISSAC [WUSCAR] 06196767 (Generated: 06/04/2024 06:12:39) Rev: 1

Contact/Location: BARRY FRKOVICH - UCCISSAC