


OIL ANALYSIS REPORT

NOT GIVEN

SULLIVAN PALATEK 23GE004286 - SIGNAL PEAK SILICA

Component Compressor



DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

All component wear rates are normal.

Contamination

There is a moderate amount of visible silt present in the sample.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06196814		
Sample Date		Client Info		15 May 2024		
Machine Age	hrs	Client Info		7233		
Oil Age	hrs	Client Info		2233		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		690		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		701		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.19		

Sullivan


OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE				
Yellow Metal	scalar	*Visual	NONE	NONE				
Precipitate	scalar	*Visual	NONE	NONE				
Silt	scalar	*Visual	NONE	MODER				
Debris	scalar	*Visual	NONE	NONE				
Sand/Dirt	scalar	*Visual	NONE	NONE				
Appearance	scalar	*Visual	NORML	NORML				
Odor	scalar	*Visual	NORML	NORML				
Emulsified Water	scalar	*Visual	>0.1	NEG				
Free Water	scalar	*Visual		NEG				
FLUID PROPERTIES method limit/base current history1 history2								
FLUID FROFERI	IES	memou	IIIIII/Dase	current	HISTORYT	HISTOLYZ		
Visc @ 40°C	cSt	ASTM D445		44.3				
SAMPLE IMAGES		method	limit/base	current	history1	history2		

Color no image no image **Bottom** no image no image **GRAPHS**

Ferrous Alloys Non-ferrous Metals











Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 **Sample No.** : UCS06196814 Lab Number : 06196814

Unique Number : 11058937

Received : 31 May 2024 Tested Diagnosed

: 03 Jun 2024

: 03 Jun 2024 - Sean Felton

GREGORY, TX US 78359 Contact: Service Manager

AIR SPECIALTY & EQUIPMENT

Test Package : IND 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRGRETX [WUSCAR] 06196814 (Generated: 06/03/2024 16:01:07) Rev: 1

Contact/Location: Service Manager - UCAIRGRETX

T:

F: