




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

219

Component

Diesel Engine

Fluid

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| SAMPLE INFORMATION | | method | limit/base | current | history1 | history2 |
|--------------------|-------------|-------------|------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | | RW0004885 | RW0004901 | RW0002964 |
| Sample Date | Client Info | | | 15 May 2024 | 12 Dec 2023 | 12 Sep 2023 |
| Machine Age | mls | Client Info | | 13412 | 7807 | 2731 |
| Oil Age | mls | Client Info | | 5605 | 5076 | 2731 |
| Oil Changed | Client Info | | | Changed | Changed | Changed |
| Sample Status | | | | NORMAL | NORMAL | ATTENTION |

| CONTAMINATION | | method | limit/base | current | history1 | history2 |
|---------------|-----------|--------|------------|----------------|----------|----------|
| Fuel | WC Method | >5 | | <1.0 | <1.0 | 0.7 |
| Water | WC Method | >0.2 | | NEG | NEG | NEG |
| Glycol | WC Method | | | NEG | NEG | NEG |

| WEAR METALS | | method | limit/base | current | history1 | history2 |
|-------------|-----|-------------|------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m | >100 | 13 | 12 | 27 |
| Chromium | ppm | ASTM D5185m | >20 | <1 | 0 | <1 |
| Nickel | ppm | ASTM D5185m | >4 | <1 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >3 | <1 | 0 | <1 |
| Aluminum | ppm | ASTM D5185m | >20 | 2 | 1 | 1 |
| Lead | ppm | ASTM D5185m | >40 | <1 | 0 | <1 |
| Copper | ppm | ASTM D5185m | >330 | 1 | <1 | 4 |
| Tin | ppm | ASTM D5185m | >15 | <1 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | <1 | 0 | <1 |

| ADDITIVES | | method | limit/base | current | history1 | history2 |
|------------|-----|-------------|------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m | 0 | 63 | 53 | 88 |
| Barium | ppm | ASTM D5185m | 0 | 2 | <1 | 9 |
| Molybdenum | ppm | ASTM D5185m | 0 | 43 | 42 | 9 |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | 2 |
| Magnesium | ppm | ASTM D5185m | 0 | 522 | 585 | 644 |
| Calcium | ppm | ASTM D5185m | | 1722 | 1929 | 1259 |
| Phosphorus | ppm | ASTM D5185m | | 850 | 887 | 715 |
| Zinc | ppm | ASTM D5185m | | 949 | 1038 | 760 |
| Sulfur | ppm | ASTM D5185m | | 2752 | 3419 | 2618 |




| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
|--------------|-----|-------------|------------|----------|----------|----------|
| Silicon | ppm | ASTM D5185m | >25 | 7 | 5 | 13 |
| Sodium | ppm | ASTM D5185m | | 2 | 2 | <1 |
| Potassium | ppm | ASTM D5185m | >20 | 2 | 1 | 7 |

| INFRA-RED | | method | limit/base | current | history1 | history2 |
|-----------|----------|-------------|------------|-------------|----------|----------|
| Soot % | % | *ASTM D7844 | >3 | 0.3 | 0.2 | 0.2 |
| Nitration | Abs/cm | *ASTM D7624 | >20 | 6.8 | 6.9 | 7.8 |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 22.4 | 21.7 | 18.0 |

| FLUID DEGRADATION | | method | limit/base | current | history1 | history2 |
|-------------------|----------|-------------|------------|-------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 20.3 | 20.3 | 13.2 |
| Base Number (BN) | mg KOH/g | ASTM D2896 | 9.4 | 9.79 | 9.21 | 11.77 |











OIL ANALYSIS REPORT



| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|--------------|-------------|----------|----------|
| Visc @ 100°C | cSt | ASTM D445 14 | 13.1 | 13.0 | 11.6 |

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RW0004885 **Received** : 31 May 2024
Lab Number : 06196868 **Tested** : 03 Jun 2024
Unique Number : 11058991 **Diagnosed** : 03 Jun 2024 - Wes Davis
Test Package : MOB 2

HOMER CONCRETE
 205 S CEDAR ST
 IMLAY CITY, MI
 US 48444
 Contact: DENNIS ONDRAJKA
 homerconcrete@aol.com
 T: (810)724-3905
 F: (810)724-0733

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)