

## **OIL ANALYSIS REPORT**

Sample Rating Trend





Machine Id MACK 10074

Component Natural Gas Engine

### Fluid PETRO CANADA 15W40 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

| SAMPLE INFORM    | <b>MATION</b> | method      | limit/base | current     | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number    |               | Client Info |            | SBP0007328  |          |          |
| Sample Date      |               | Client Info |            | 30 May 2024 |          |          |
| Machine Age      | hrs           | Client Info |            | 7607        |          |          |
| Oil Age          | hrs           | Client Info |            | 440         |          |          |
| Oil Changed      |               | Client Info |            | Changed     |          |          |
| Sample Status    |               |             |            | NORMAL      |          |          |
| CONTAMINATIO     | N             | method      | limit/base | current     | history1 | history2 |
| Water            |               | WC Method   | >0.1       | NEG         |          |          |
| WEAR METALS      |               | method      | limit/base | current     | history1 | history2 |
| Iron             | ppm           | ASTM D5185m | >50        | 10          |          |          |
| Chromium         | ppm           | ASTM D5185m | >5         | <1          |          |          |
| Nickel           | ppm           | ASTM D5185m | >4         | <1          |          |          |
| Titanium         | ppm           | ASTM D5185m | >5         | <1          |          |          |
| Silver           | ppm           | ASTM D5185m | >3         | 0           |          |          |
| Aluminum         | ppm           | ASTM D5185m | >25        | 5           |          |          |
| Lead             | ppm           | ASTM D5185m | >40        | 2           |          |          |
| Copper           | ppm           | ASTM D5185m | >150       | <1          |          |          |
| Tin              | ppm           | ASTM D5185m | >4         | <1          |          |          |
| Vanadium         | ppm           | ASTM D5185m |            | <1          |          |          |
| Cadmium          | ppm           | ASTM D5185m |            | <1          |          |          |
| ADDITIVES        |               | method      | limit/base | current     | history1 | history2 |
| Boron            | ppm           | ASTM D5185m |            | 6           |          |          |
| Barium           | ppm           | ASTM D5185m |            | 0           |          |          |
| Molybdenum       | ppm           | ASTM D5185m |            | 54          |          |          |
| Manganese        | ppm           | ASTM D5185m |            | <1          |          |          |
| Magnesium        | ppm           | ASTM D5185m |            | 541         |          |          |
| Calcium          | ppm           | ASTM D5185m |            | 1592        |          |          |
| Phosphorus       | ppm           | ASTM D5185m |            | 742         |          |          |
| Zinc             | ppm           | ASTM D5185m |            | 961         |          |          |
| Sulfur           | ppm           | ASTM D5185m |            | 2501        |          |          |
| CONTAMINANTS     | \$            | method      | limit/base | current     | history1 | history2 |
| Silicon          | ppm           | ASTM D5185m | >25        | 15          |          |          |
| Sodium           | ppm           | ASTM D5185m |            | 4           |          |          |
| Potassium        | ppm           | ASTM D5185m | >20        | 4           |          |          |
| INFRA-RED        |               | method      | limit/base | current     | history1 | history2 |
| Soot %           | %             | *ASTM D7844 |            | 0           |          |          |
| Nitration        | Abs/cm        | *ASTM D7624 | >20        | 11.0        |          |          |
| Sulfation        | Abs/.1mm      | *ASTM D7415 | >30        | 22.9        |          |          |
| FLUID DEGRADA    | ATION         | method      | limit/base | current     | history1 | history2 |
| Oxidation        | Abs/.1mm      | *ASTM D7414 | >25        | 19.9        |          |          |
| Base Number (BN) | mg KOH/g      | ASTM D2896  |            | 4.0         |          |          |
| , ,              |               |             |            |             |          |          |



35 30

u<sup>25</sup> 4ps/cm 20

15 10 May30/24

Base Number (mg KOH/g) 2.5 1.0 1.5

0.5 0.0 May30/24

19 18 Abnorm 17-13 Abnorm 12

Base 4.0 3.5

# **OIL ANALYSIS REPORT**

| FT-IR (Direct Trend)  | VISUAL                           |                            | method                       | limit/base                             | current    | history1 | history2   |
|---|----------------------------------|----------------------------|------------------------------|--|------------|----------|--|
| Oxidation<br>0.   | White Metal                      | scalar                     | *Visual                      | NONE                                   | NONE       |          |  |
| sussesses Sulfation   | Yellow Metal                     |                            | *Visual                      | NONE                                   | NONE       |          |  |
| 5 - Abnormal  | Precipitate                      |                            | *Visual                      | NONE                                   | NONE       |          |  |
| 0   | Silt                             |                            | *Visual                      | NONE                                   | NONE       |          |  |
| 5-  | Debris                           | scalar                     | *Visual                      | NONE                                   | NONE       |          |  |
| 0   | Sand/Dirt                        | scalar                     | *Visual                      | NONE                                   | NONE       |          |  |
| May30/24<br>May30/24  | Appearance                       | scalar                     | *Visual                      | NORML                                  | NORML      |          |  |
| May   | Odor                             | scalar                     | *Visual                      | NORML                                  | NORML      |          |  |
| Base Number   | Emulsified Water                 | scalar                     | *Visual                      | >0.1                                   | NEG        |          |  |
| -   | Free Water                       | scalar                     | *Visual                      |  | NEG        |          |  |
| 5+<br>0+  | FLUID PROPERT                    | IES                        | method                       | limit/base                             | current    | history1 | history2   |
| 5-  | Visc @ 100°C                     | cSt                        | ASTM D445                    |  | 15.0       |          |  |
| 5-  | GRAPHS                           |                            |                              |  |            |          |  |
| 0   | Ferrous Alloys                   |                            |                              |  |            |          |  |
| 0   | <sup>10</sup> L                  |                            |                              | -                                      |            |          |  |
| May30/24  | 8 - iron                         |                            |                              |  |            |          |  |
| .~-w<br>₩   | nickel                           |                            |                              |  |            |          |  |
| Viscosity @ 100°C   | 6 -<br>Ed.                       |                            |                              |  |            |          |  |
| 9<br>]  | 8.4                              |                            |                              |  |            |          |  |
| 8 - Abnormal  |                                  |                            |                              |  |            |          |  |
| 6   | 2                                |                            |                              |  |            |          |  |
| 51  |                                  |                            |                              |  |            |          |  |
| 4 -<br>3 - Abnormal   | May30/24                         |                            |                              | May30/24                               |            |          |  |
| 2 +   |                                  |                            |                              | Mar                                    |            |          |  |
| 24  | Non-ferrous Metals               | S                          |                              |  |            |          |  |
| May30/24<br>лслс.—м   | copper                           |                            |                              |  |            |          |  |
| ۷ ۷   | 8 - management tin               |                            |                              |  |            |          |  |
|   | 6-                               |                            |                              |  |            |          |  |
|   | u dd                             |                            |                              |  |            |          |  |
|   | 4                                |                            |                              |  |            |          |  |
|   | 2-                               |                            |                              |  |            |          |  |
|   |                                  |                            |                              |  |            |          |  |
|   | 30/24                            |                            |                              | ay30/24 -                              |            |          |  |
|   | May3                             |                            |                              | May3                                   |            |          |  |
|   | Viscosity @ 100°C                |                            |                              |  | Base Numbe | er       |  |
|   | 19                               |                            |                              | 4.0                                    |            |          | -  |
|   | 18<br>Abnormal                   |                            |                              | 3.5                                    | -          |          |  |
|   |                                  |                            |                              | (B/HO)                                 | 1          |          |  |
|   | () 16<br>() 15<br>() 15<br>() 14 |                            |                              | ()<br>HOX 2.5-<br>bg 2.0-<br>grad 1.5- |            |          |  |
|   | ts <sup>2</sup> 14               |                            |                              | 15 2.0                                 |            |          |  |
|   | 13 - Abnormal                    |                            |                              | 2 1.5<br>88<br>1.0                     |            |          |  |
|   | 12 -                             |                            |                              | 0.5                                    |            |          |  |
|   | 11                               |                            |                              |  |            |          |  |
|   | May30/24                         |                            |                              | May30/24                               | May30/24   |          | May30/24   |
|   | Ma                               |                            |                              | Mar                                    | Ma         |          | May  |
|   | : 11059485<br>: FLEET            | Receiv<br>Tested<br>Diagno | ed : 03<br>: 04<br>osed : 04 | Jun 2024<br>Jun 2024<br>Jun 2024 - We  | es Davis   |          | 02 N 16TH ST<br>OMAHA, NE<br>US 68110<br>: TROY BEAN |
| Automatical and the second s | are outside of the ISO 17        | 7025 scop                  | e of accred                  | itation.                               |            | -        | T:<br>F:   |

Submitted By: TROY BEAN

Page 2 of 2