

# **OIL ANALYSIS REPORT**

Area S-46 [285290] PALATEK 1301160002 - RODE WELDING Component Compressor

### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear


All component wear rates are normal.

## Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend



NORMAL

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0001061		
Sample Date		Client Info		26 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		1		
Phosphorus	ppm	ASTM D5185m		278		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		0		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		8		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.18		



# **OIL ANALYSIS REPORT**

Acid Number 0.20 (B/H0.15 Acid Number (mg K 0.02 0.00 Apr26/24 -Apr26/24 Viscosity @ 40°C 52 Abnormal 50 48 (0-0<del>4</del>6 tso 42 40 Abnom 38 Apr26/24 Apr26/24

	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Apr26/24	Appearance	scalar	*Visual	NORML	NORML			
Ap	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERTI	IES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445		45.3			
	SAMPLE IMAGES		method	limit/base	current	history1	history2	
Api26/24	Color					no image	no image	
	Bottom					no image	no image	
	Ferrous Alloys			Apr26/24				
	8 6 4 2 0 4 7 10 7 10 7 10 7 10 7 10 7 10 7 10			Apr26/24				
	Viscosity @ 40°C			5.0 1.0 Million (00 2.0 Million (00 2.0 View	Acid Numbe	r		
Laboratory Sample No. Lab Number Unique Number	: WearCheck USA - 501 : UFD0001061 : 06197792	Rece Teste	son Ave., Cary, NC 27513 eived : 03 Jun 2024			<b>FLUID-AIRE DYNAMIC</b> 225 SPRING LAKE D ITASCA, US 6014		
entificate 12367 Test Package o discuss this sample report - Denotes test methods that tatements of conformity to s	: IND 2 , contact Customer Servic are outside of the ISO 17	ce at 1-8 7025 sco	300-237-1369 ope of accred	9. litation.	eo	d.diener@fluidair T:	ct: ED DIENE	

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ED DIENER - UCFLUSCH

F: