

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

## Machine Id **TOTE 123** Component **New (Unused) Oil** Fluid **{not provided} (--- GAL)**

## DIAGNOSIS

Recommendation

This is a baseline read-out on the submitted sample.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TLC0001675		
Sample Date		Client Info		19 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>5	0		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m	>5	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>5	0		
Aluminum	ppm	ASTM D5185m	>5	1		
Lead	ppm	ASTM D5185m	>5	1		
Copper	ppm	ASTM D5185m	>5	0		
Tin	ppm	ASTM D5185m	>5	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		245		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		44		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		232		
Calcium	ppm	ASTM D5185m		929		
Phosphorus	ppm	ASTM D5185m		857		
Zinc	ppm	ASTM D5185m		949		
Sulfur	ppm	ASTM D5185m		4073		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	5		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	4		
Water	%	ASTM D6304		NEG		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	2461		
Particles >6µm		ASTM D7647	>1300	379		
Particles >14µm		ASTM D7647	>160	8		
Particles >21µm		ASTM D7647	>40	1		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/16/10		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.53		



## **OIL ANALYSIS REPORT**

Particle Trend	VISUAL		method	limit/base	current	history1	history2
Ponomai 4µm	White Metal	scalar	*Visual	NONE	NONE		
14μm	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Apr19/24 Apr19/24	Appearance	scalar	*Visual	NORML	NORML		
Apr	Odor	scalar	*Visual	NORML	NORML		
Acid Number	Emulsified Water	scalar	*Visual		NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		78.65		
	Visc @ 100°C	cSt	ASTM D445		11.95		
	Viscosity Index (VI)	Scale	ASTM D2270		146		
	SAMPLE IMAGES			limit/bass		biotonut	history
Apri 9/24 - Apri 9/24 - Apri 9/24 -		5	method	limit/base	current	history1	history2
₹ Viscosity @ 40°C Abnormal	Color				•	no image	no image
Abnomal	Bottom					no image	no image
Viscosity @ 100°C	Non-ferrous Metal			42/61/142 42/61/142 48/ 48/ 48/ 48/ 48/ 48/ 48/ 48/ 48/ 48/	Abnormal	14μ 21μ	-2 +2 +2 +2 +2 +1 +1 +1 +1 +1 +1 $+38\mu$ $-71\mu$
	120 110 (1) 100 (1) 100 (1) 100 80 70 +70 616 100 +70 +70 616 100			Apr19/24 Acid Number (mg KOH(g) 1.0 1.0 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1	Apr19/24		
Unique Numbe Certificate L2367 Test Package	: WearCheck USA - 50 : TLC0001675 r : 06198111 r : 11060234 e : PLANT ( Additional Te t, contact Customer Servi	Rece Teste Diagr ests: FT-	ived : 03 d : 03 nosed : 05 IR, ICP-New	3 Jun 2024 5 Jun 2024 Jun 2024 - Jona Oil, KV100, N			

Contact/Location: MICHAEL JACKSON - SUPATLGA