

# **OIL ANALYSIS REPORT**

Sample Rating Trend

SAMPLE INFORMATION method limit/base



NORMAL



MINING ME-56 VOLVO L350F ME-56

Component Front Differential

# Fluid SHELL Spirax S4 CX 30 (--- GAL)

### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

Area

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


## Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM		method	iinii/base	current	riistory i	nistory2
Sample Number		Client Info		WC0939957		
Sample Date		Client Info		29 May 2024		
Machine Age	hrs	Client Info		11775		
Oil Age	hrs	Client Info		1500		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	41		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>100	3		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		87		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		3		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		26		
Calcium	ppm	ASTM D5185m		2863		
Phosphorus	ppm	ASTM D5185m		1230		
Zinc	ppm	ASTM D5185m		1342		
Sulfur	ppm	ASTM D5185m		6025		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	10		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	2		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>.2	NEG		
Free Water	scalar	*Visual		NEG		
:13:17) Rev: 1					Submitted E	y: Grant Wilson



# **OIL ANALYSIS REPORT**



FLUID PROPERT	IES method		current	history1	history2
Visc @ 40°C	cSt ASTM D4	45 93.9	68.6		
SAMPLE IMAGES	s method	d limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image
GRAPHS					
Ferrous Alloys					
40 35 30 25 20 15 10 5 0 40 25 10 5 10 10 10 10 10 10 10 10 10 10	5	May29.24			
Viscosity @ 40°C		May29/24 +			
150 Abnormal 150 -					
130 (3120 (3120 (3100 (3100 (300) (30)					
<sup>80</sup> Abnormal					
60 42		24			
May29/24		May29/24			
y : WearCheck USA - 501 b. : WC0939957 er : 06198436 ber : 11060559 ge : CONST	Received Tested			l L	<b>ESUEUR - 008</b> DTTAWA ROAD LE SUEUR, MN JS 56058-4292 ct: Sam Donner



\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (507)931-6081

F:

samuel.donner@coviacorp.com