

OIL ANALYSIS REPORT

Area SULLUBE **ATLAS COPCO API630444 - GREAT PLAINS ABW** Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06199384		
Sample Date		Client Info		22 May 2024		
Machine Age	hrs	Client Info		9119		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	<1		
Copper	ppm	ASTM D5185m	>65	3		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	500	3		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		<1		
Phosphorus	ppm	ASTM D5185m		20		
Zinc	ppm	ASTM D5185m		20		
Sulfur	ppm	ASTM D5185m	150	64		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	<1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.5	0.50		



OIL ANALYSIS REPORT



VIS	UAL		method	limit/base	current	history1	history2	
	e Metal	scalar	*Visual	NONE	NONE			
Yello	w Metal	scalar	*Visual	NONE	NONE			
Preci	pitate	scalar	*Visual	NONE	NONE			
Silt		scalar	*Visual	NONE	NONE			
Debri	s	scalar	*Visual	NONE	NONE			
Sand	/Dirt	scalar	*Visual	NONE	NONE			
Appe Odor	arance	scalar	*Visual	NORML	NORML			
Mar Odor		scalar	*Visual	NORML	NORML			
Emul	sified Water	scalar	*Visual	>0.1	NEG			
Free	Water	scalar	*Visual		NEG			
FLU	JID PROPERTI	ES	method	limit/base	current	history1	history2	
Visc	@ 40°C	cSt	ASTM D445	36	49.1			
SA	MPLE IMAGES		method	limit/base	current	history1	history2	
+77272/eW Color						no image	no image	
Botto	m					no image	no image	
	n-ferrous Metals			May2224				
Visc 55 				(0,0.60 (0,0.48 (0,0.48) (0,0.40 (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.48) (0,0.4	Acid Number		400000	
Laboratory : WearC Sample No. : UCH06 Lab Number : 061993 Unique Number : 110615 Test Package : IND 2	6199384 <mark>384</mark> 507	Madison Ave., Cary, NC 27513 Received : 04 Jun 2024 Tested : 05 Jun 2024 Diagnosed : 06 Jun 2024 - Wes Davis the at 1-800-237-1369. 2025 scope of accreditation. In the simple acceptance decision rule (JCG.			ŀ	AIR CAPITAL EQUIPMENT INC 806 E BOSTON ST WICHITA, KS US 67211 Contact: MIKAYLA STOUT mstout@aircapeq.com T: (316)522-1111		

Contact/Location: MIKAYLA STOUT - UCAIRWIC