

OIL ANALYSIS REPORT

Area SULLUBE [1120364] SULLAIR 003-106722 - GREAT PLAINS ASSARIA EAST Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend



NORMAL

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06199397		
Sample Date		Client Info		06 May 2024		
Machine Age	hrs	Client Info		42985		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	<1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	500	693		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		1		
Calcium	ppm	ASTM D5185m		2		
Phosphorus	ppm	ASTM D5185m		<1		
Zinc	ppm	ASTM D5185m		<1		
Sulfur	ppm	ASTM D5185m	150	328		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m		17		
Potassium	ppm	ASTM D5185m	>20	5		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.5	0.085		




Base 35 Abnormal

30 May6/24

DX#

OIL ANALYSIS REPORT

VISUAL



	VISUAL		method	iiiiii/base	current	nistory i	Thistory2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
4	Sand/Dirt	scalar	*Visual	NONE	NONE		
May6/24	Appearance	scalar	*Visual	NORML	NORML		
2	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	36	38.7		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
May6/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta	ıls		4 May6/24			
	Viscosity @ 40°C			May624 (0.60 Acid Number (ng K0H(d) Acid Numb	Acid Number		
	: WearCheck USA - 50 : UCH06199397 : 06199397 : 11061520	Rece Teste Diagr		AIR CAPITAL EQUIPMENT II 806 E BOSTON WICHITA, US 672 Contact: MIKAYLA STO mstout@aircapeq.cr T: (316)522-11 M 106:2012)			

Report Id: UCAIRWIC [WUSCAR] 06199397 (Generated: 06/05/2024 14:37:55) Rev: 1

Contact/Location: MIKAYLA STOUT - UCAIRWIC