


OIL ANALYSIS REPORT

MINING

ME-124 JOHN DEERE 844L 1DW844LXKLF706566

Front Differential

SHELL Spirax S4 CX 30 (--- GAL)



DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

Bearing and/or bushing wear is indicated. All other component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The condition of the oil is acceptable for the time in service.


| OAMBLE INCOM | ATION | | 11 11 11 | | | 12. |
|------------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFORM | ATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0920498 | | |
| Sample Date | | Client Info | | 09 May 2024 | | |
| Machine Age | hrs | Client Info | | 8198 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | ABNORMAL | | |
| CONTAMINATION | l | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >.2 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >500 | 341 | | |
| Chromium | ppm | ASTM D5185m | >10 | 2 | | |
| Nickel | ppm | ASTM D5185m | >10 | <1 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 1 | | |
| Lead | ppm | ASTM D5185m | >25 | 3 | | |
| Copper | ppm | ASTM D5185m | >100 | 142 | | |
| Tin | ppm | ASTM D5185m | >10 | 2 | | |
| Vanadium | ppm | ASTM D5185m | | - <1 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| | PP | | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 2 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 3 | | |
| Manganese | ppm | ASTM D5185m | | 5 | | |
| Magnesium | ppm | ASTM D5185m | | 83 | | |
| Calcium | ppm | ASTM D5185m | | 3185 | | |
| Phosphorus | ppm | ASTM D5185m | | 983 | | |
| Zinc | ppm | ASTM D5185m | | 1004 | | |
| Sulfur | ppm | ASTM D5185m | | 3742 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >75 | 10 | | |
| Sodium | ppm | ASTM D5185m | | 2 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >.2 | NEG | | |
| | | | | | | |
| Free Water | scalar | *Visual | | NEG | | |





OIL ANALYSIS REPORT



| FLUID PROPERTIES | | method | limit/base | current | history1 | history2 |
|------------------|-----|-----------|------------|----------|----------|----------|
| Visc @ 40°C | cSt | ASTM D445 | 93.9 | 51.6 | | |
| SAMPLE IMAGES | | method | limit/base | current | history1 | history2 |
| Color | | | | no image | no image | no image |
| Bottom | | | | no image | no image | no image |
| GRAPHS | | | | | | |









Certificate 12367

Test Package : CONST

Sample No. : WC0920498 Lab Number : 06199604 Unique Number : 11061727

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 04 Jun 2024 Tested : 05 Jun 2024 Diagnosed

: 06 Jun 2024 - Don Baldridge

COVIA - JUNCTION CITY - 095 1333 SANDPIT ROAD

MAUK, GA US 31058

Contact: Phil Ivanisin phil.ivanisin@coviacorp.com T: (478)244-7020

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Phil Ivanisin - COVJUN