




# OIL ANALYSIS REPORT

## Sample Rating Trend



**NORMAL**



Machine Id

**I-1**

Component

**Gearbox**

Fluid

**SHELL OMALA S2 GX 220 (--- GAL)**

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0917253</b>	WC0868172	WC0831563
Sample Date	Client Info			<b>03 Jun 2024</b>	29 Jan 2024	16 Oct 2023
Machine Age	hrs	Client Info		<b>0</b>	0	0
Oil Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed	Client Info			<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>0.2	<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	<b>12</b>	19	12
Chromium	ppm	ASTM D5185m	>10	<b>0</b>	<1	0
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>25	<b>0</b>	2	0
Lead	ppm	ASTM D5185m	>50	<b>&lt;1</b>	2	<1
Copper	ppm	ASTM D5185m	>200	<b>8</b>	9	6
Tin	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	1	<1


ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	6.2	<b>0</b>	2	1
Barium	ppm	ASTM D5185m	0.0	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m	0	<b>1</b>	<1	0
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	1	1
Magnesium	ppm	ASTM D5185m	0	<b>1</b>	1	13
Calcium	ppm	ASTM D5185m	0.0	<b>42</b>	<1	1
Phosphorus	ppm	ASTM D5185m	290	<b>220</b>	283	166
Zinc	ppm	ASTM D5185m	3.8	<b>36</b>	14	0
Sulfur	ppm	ASTM D5185m	8167	<b>13076</b>	18640	9347

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<b>0</b>	2	1
Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	3
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	3	<1

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual		<b>NEG</b>	NEG	NEG











# OIL ANALYSIS REPORT



FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	220	<b>200</b>	200	199

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0917253      **Received** : 04 Jun 2024  
**Lab Number** : 06199606      **Tested** : 05 Jun 2024  
**Unique Number** : 11061729      **Diagnosed** : 05 Jun 2024 - Wes Davis  
**Test Package** : MOB 1

**UNITED TOOL & STAMPING**  
 2817 ENTERPRISE AVE  
 FAYETTEVILLE, NC  
 US 28306  
 Contact: KENNY BELL  
 KENNY.BELL@UTS-NC.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: