

OIL ANALYSIS REPORT

Sample Rating Trend







WHEY
Machine Id
WS08
Component
Lube System
Fluid

MOBIL DTE 25 (3 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.


| | | | Nov2023 | May2024 | | |
|------------------|--------|-------------|------------|-------------|-------------|------------|
| SAMPLE INFORM | 1ATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0927416 | WC0864109 | |
| Sample Date | | Client Info | | 21 May 2024 | 19 Nov 2023 | |
| Machine Age | hrs | Client Info | | 0 | 0 | |
| Oil Age | hrs | Client Info | | 0 | 0 | |
| Oil Changed | | Client Info | | N/A | N/A | |
| Sample Status | | | | NORMAL | ATTENTION | |
| CONTAMINATION | ١ | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.05 | NEG | NEG | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Chromium | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Nickel | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Titanium | ppm | ASTM D5185m | | 0 | <1 | |
| Silver | ppm | ASTM D5185m | | 0 | 0 | |
| Aluminum | ppm | ASTM D5185m | >20 | 0 | 1 | |
| Lead | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Copper | ppm | ASTM D5185m | >20 | <1 | 2 | |
| Tin | ppm | ASTM D5185m | >20 | 0 | 0 | |
| Vanadium | ppm | ASTM D5185m | 720 | <1 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| | рріні | | | - | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | |
| Barium | ppm | ASTM D5185m | | 0 | 0 | |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | |
| Magnesium | ppm | ASTM D5185m | | 0 | <1 | |
| Calcium | ppm | ASTM D5185m | | 51 | 58 | |
| Phosphorus | ppm | ASTM D5185m | | 307 | 324 | |
| Zinc | ppm | ASTM D5185m | | 499 | 467 | |
| Sulfur | ppm | ASTM D5185m | | 750 | 743 | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >15 | <1 | <1 | |
| Sodium | ppm | ASTM D5185m | | 1 | 0 | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | 2 | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | NONE | |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | |
| Silt | scalar | *Visual | NONE | NONE | NONE | |
| Debris | scalar | *Visual | NONE | NONE | NONE | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | |
| Appearance | scalar | *Visual | NORML | NORML | NORML | |
| Odor | scalar | *Visual | NORML | NORML | NORML | |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | NEG | |
| Free Water | scalar | *Visual | . 0.00 | NEG | NEG | |
| 9:51:10) Dov: 2 | Julia | Violati | | Cubmitt | | VILLAGENOR |





OIL ANALYSIS REPORT















Certificate 12367

Laboratory

Sample No. : WC0927416 Lab Number : 06199703

Unique Number : 11061826 Test Package : IND 1

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 04 Jun 2024 : 05 Jun 2024

Tested Diagnosed

: 06 Jun 2024 - Doug Bogart

LEPRINO FOODS-GREELEY

1302 1ST AVE GREELEY, CO US 80631-5909

Contact: ERIC KLINE EKLINE@LEPRINOFOODS.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (970)347-5190

Submitted By: MICHAEL VILLASENOR