




OIL ANALYSIS REPORT



Area
OKLAHOMA/102/EG - DOZER
 Machine Id
39.61 [OKLAHOMA^102^EG - DOZER]
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0908914	WC0873886	WC0807994
Sample Date	Client Info			28 May 2024	10 Nov 2023	01 May 2023
Machine Age	hrs	Client Info		9900	9660	9390
Oil Age	hrs	Client Info		240	270	343
Oil Changed	Client Info			Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method			<1.0	<1.0	<1.0
Water	WC Method			NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m		19	30	37
Chromium	ppm	ASTM D5185m		<1	<1	1
Nickel	ppm	ASTM D5185m		0	0	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m		2	1	2
Lead	ppm	ASTM D5185m		0	2	4
Copper	ppm	ASTM D5185m		3	3	4
Tin	ppm	ASTM D5185m		0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		47	45	43
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		38	42	43
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		482	490	485
Calcium	ppm	ASTM D5185m		1727	1686	1723
Phosphorus	ppm	ASTM D5185m		738	729	744
Zinc	ppm	ASTM D5185m		890	911	911
Sulfur	ppm	ASTM D5185m		2821	2522	2473

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		6	5	6
Sodium	ppm	ASTM D5185m		2	0	1
Potassium	ppm	ASTM D5185m		0	2	<1


INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0.4	0.5	0.6
Nitration	Abs/cm	*ASTM D7624		7.7	9.1	10.2
Sulfation	Abs/.1mm	*ASTM D7415		22.3	23.5	24.5

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414		20.2	21.6	23.1
Base Number (BN)	mg KOH/g	ASTM D2896		9.6	8.9	9.4




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	NEG	NEG	NEG
Free Water	scalar	*Visual	NEG	NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.2	12.4	12.5

GRAPHS


Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0908914 **Received** : 05 Jun 2024
Lab Number : 06199937 **Tested** : 06 Jun 2024
Unique Number : 11062060 **Diagnosed** : 06 Jun 2024 - Wes Davis
Test Package : CONST (Additional Tests: TBN)

SHERWOOD CONSTRUCTION CO INC
 3219 WEST MAY ST
 WICHITA, KS
 US 67213
 Contact: DOUG KING
 doug.king@sherwood.net
 T: (316)617-3161
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)