


OIL ANALYSIS REPORT

OKLAHOMA/102/EG - BACKHOE LOADER 53.510L [OKLAHOMA^102^EG - BACKHOE LOADER]

Diesel Engine

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)





DIAGNOSIS

Recommendation

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0935201	WC0935195	WC0874000
Sample Date		Client Info		14 May 2024	08 May 2024	15 Feb 2024
Machine Age	hrs	Client Info		8215	10281	10030
Oil Age	hrs	Client Info		250	250	258
Oil Changed	1110	Client Info		Changed	Changed	Changed
Sample Status		Ollerit IIIIO		ABNORMAL	NORMAL	ATTENTION
·						
CONTAMINATION	١	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	1.7
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	73	36	21
Chromium	ppm	ASTM D5185m	>20	6	<1	1
Nickel	ppm	ASTM D5185m	>2	0	0	1
Titanium	ppm	ASTM D5185m	>2	1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	<u> </u>	2	2
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm	ASTM D5185m	>330	8	4	2
Tin	ppm	ASTM D5185m	>15	0	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	85	57	60
Barium	ppm	ASTM D5185m	0	0	0	1
Molybdenum	ppm	ASTM D5185m	0	38	48	60
Manganese	ppm	ASTM D5185m		1	<1	1
Magnesium	ppm	ASTM D5185m	0	473	490	442
Calcium	ppm	ASTM D5185m		2232	1723	1651
Phosphorus	ppm	ASTM D5185m		912	764	751
Zinc	ppm	ASTM D5185m		1130	907	921
Sulfur	ppm	ASTM D5185m		3434	2929	2805
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	▲ 60	8	8
Sodium	ppm	ASTM D5185m		3	11	13
Potassium	ppm	ASTM D5185m	>20	5	0	2
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3	0.6	0.6
Nitration	Abs/cm	*ASTM D7624	>20	9.6	8.9	8.1
			>30	23.3	22.5	20.8
Sulfation	Abs/.1mm	*ASTM D7415	/00	23.3	22.0	20.0
			limit/base	current		history2
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
			limit/base >25			




OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


I LOID I HOI LI	THES	memou	IIIIIII Dase	Culterit	HISTORY	Historyz
Visc @ 100°C	cSt	ASTM D445	14	14.4	12.6	12.2


GRAPHS

Non-formus Motals

Ferrous Alloys 60 mdd 50 30 20

20-	*****	copper lead tin							
15-		٨							
5		1		1	1				1
	V	1	A_{-}	1	7	-	\Rightarrow	~	/
Aug23/11	Jun19/12	Oct9/13	Apr3/15	Jan 13/17	Apr14/18	Sep13/19	Jul21/21	Oct26/22	May8/24









Certificate 12367

Laboratory Sample No.

: WC0935201 Lab Number : 06199963 Unique Number : 11062086

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 05 Jun 2024 **Tested**

: 06 Jun 2024 Diagnosed : 07 Jun 2024 - Sean Felton Test Package : CONST (Additional Tests: TBN)

SHERWOOD CONSTRUCTION CO INC 3219 WEST MAY ST WICHITA, KS

US 67213 Contact: DOUG KING doug.king@sherwood.net T: (316)617-3161

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: