

OIL ANALYSIS REPORT

Area DURATECH HI ATLAS COPCO API254676 - STEELVILLE MANUFACTURING BLD 2 Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06200311	UCH06056792	
Sample Date		Client Info		16 May 2024	29 Nov 2023	
Machine Age	hrs	Client Info		15902	15516	
Oil Age	hrs	Client Info		400	13271	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	ABNORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	
Chromium	ppm	ASTM D5185m	>5	0	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>15	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	
Copper	ppm	ASTM D5185m	>65	6	2	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		<1	0	
Calcium	ppm	ASTM D5185m		0	0	
Phosphorus	ppm	ASTM D5185m		313	34	
Zinc	ppm	ASTM D5185m		152	16	
Sulfur	ppm	ASTM D5185m		309	75	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	4	2	
Sodium	ppm	ASTM D5185m		4	0	
Potassium	ppm	ASTM D5185m	>20	0	0	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.53	0.19	



OIL ANALYSIS REPORT

VISUAL



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	LIGHT	A MODER	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
5/24 -	Appearance	scalar	*Visual	NORML	NORML	NORML	
May16/24	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT			limit/bass		biotomid	history ()
			method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		46.2	48.9	
	SAMPLE IMAGES	S j	method	limit/base	current	history1	history2
May16/24 -	Color					ALE	no image
	Bottom						no image
	Non-ferrous Metal	S		May16/24 May16/24			
	No						
	² Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C			(^{0.60}			
	Viscosity @ 40°C			(^{0,60}) (⁰⁾ HO 0.48 @ 0.38			
	Viscosity @ 40°C			() () () () () () () () () () () () () (
	Viscosity @ 40°C			(B) 0.60 HOX 0.48 D 0.36 quart 0.24 V 0.12			
	Viscosity @ 40°C			(0,0.60 0,0.46 0,0.36 0,0.24 0,0.36 0,0.24 0,0.0 0,0.2 0,0.2 0,0.0			
	Viscosity @ 40°C			(0,0.60 0,0.00 0,0.00 0,0.00 0,0.0 0,00 0,0			200

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: JOSH DYRLAND - UCHTESTL

F: (314)731-4424