


# **PROBLEM SUMMARY**

Sample Rating Trend




Machine Id

# **FERRARA LADDER 1**

Hydraulic System

AW HYDRAULIC OIL ISO 22 (--- GAL)

## COMPONENT CONDITION SUMMARY



### RECOMMENDATION

We advise that you check all areas where dirt can enter the system. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS						
Sample Status				SEVERE		
Silicon	ppm	ASTM D5185m	>20	<b>394</b>		

Customer Id: BOSBOSLA
Sample No.: WC0930956
Lab Number: 06200961
Test Package: FLEET

To manage this report scan the QR code

To discuss the diagnosis or test data:
Don Baldridge +1
don.b505@comcast.net

To change component or sample information:
Customer Service +1 1-800-237-1369
customerservice@wearcheck.com

RECOMMENDED A	ACTIONS			
Action	Status	Date	Done By	Description
Check Dirt Access			2	We advise that you check all areas where dirt can enter the system.

# HISTORICAL DIAGNOSIS



# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# **FERRARA LADDER 1**

Component
Hydraulic System

**AW HYDRAULIC OIL ISO 22 (--- GAL)** 

## DIAGNOSIS

#### Recommendation

We advise that you check all areas where dirt can enter the system. Resample at the next service interval to monitor.

All component wear rates are normal.

## Contamination

Elemental level of silicon (Si) above normal indicating ingress of dirt/seal material.

#### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

				May2024		
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0930956		
Sample Date		Client Info		08 May 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed	0	Client Info		Not Changd		
Sample Status				SEVERE		
CONTAMINATIO	ON	method	limit/base	current	history1	history2
Water	-	WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel			>10	<1		
Titanium	ppm		>10			
	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	4		
Lead	ppm	ASTM D5185m	>10	<1		
Copper	ppm	ASTM D5185m	>75	4		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0		
Barium	ppm	ASTM D5185m	5	1		
Molybdenum	ppm	ASTM D5185m	5	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	25	12		
Calcium	ppm	ASTM D5185m	200	73		
Phosphorus	ppm	ASTM D5185m	300	430		
Zinc	ppm	ASTM D5185m	370	443		
Sulfur	ppm	ASTM D5185m	2500	1052		
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	▲ 394		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	1		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
			<b>&gt;</b> 0.1			
Free Water	scalar	*Visual		NEG		

Contact/Location: K JOHNSON - BOSBOSLA



## **OIL ANALYSIS REPORT**



Non-ferrous Metals

Viscosity @ 40°C





Certificate 12367

Laboratory

Sample No. : WC0930956 Lab Number : 06200961 Unique Number : 11063084

Test Package : FLEET

> 20 19 18

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 05 Jun 2024 Tested : 06 Jun 2024

Diagnosed : 08 Jun 2024 - Don Baldridge

Contact: K JOHNSON JOHNSONK@FIRESERVERRO.COM T:

**BOSSIER CITY FIRE DEPT** 

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: BOSBOSLA [WUSCAR] 06200961 (Generated: 06/08/2024 11:48:12) Rev: 1

Contact/Location: K JOHNSON - BOSBOSLA

5850 SHED RD

US 71111

F:

BOSSIER CITY, LA

no image

no image

no image

no image