

FUEL REPORT

[PMOAS3139178] 174947

Component **Diesel Fuel**

No.2 DIESEL FUEL (HIGH-SULPHUR) (--- GAL)

Sample Rating Trend



Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 diesel fuel.

Corrosion

All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. There is no indication of any contamination in the fuel.


Fuel Condition

Sulfur value derived by ASTM D5453 method for ULSD validation.


iAL)		Apr202	1 Apr2022	Apr2023 M	ay2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number Sample Date		Client Info		DC0036994 20 May 2024	DC0029057 18 Apr 2023	DC0019533 20 Apr 2022
Machine Age	hrs	Client Info		1169	1132	1102
Sample Status				NORMAL	NORMAL	NORMAL
PHYSICAL PROF	PERTIES	method	limit/base	current	history1	history2
ASTM Color	scalar	*ASTM D1500		L5.0	L4.5	L5.5
Visc @ 40°C	cSt	ASTM D445	3.0	2.67	2.59	2.64
SULFUR CONTENT		method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m	500	891	421	702
Sulfur (UVF)	ppm	ASTM D5453	000	885	683	689
IGNITION QUALI		method	limit/base			
	I T			current	history1	history2
API Gravity		ASTM D7777	37.7	34.9	34.9	34.9
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	<1	0	4
Sodium	ppm	ASTM D5185m	<0.1	1	<1	0
Potassium	ppm	ASTM D5185m	<0.1	2	0	<1
Water	%	ASTM D6304	< 0.05	0.003	0.004	0.002
ppm Water	ppm	ASTM D6304	<500	31	42.7	19.8
% Gasoline	%	*In-House	< 0.50	0.0	0.0	0.0
% Biodiesel	%	*In-House	<20.0	0.0	0.0	0.0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>2500		1671	3001
Particles >6µm		ASTM D7647	>640		624	787
Particles >14μm		ASTM D7647	>80		68	74
Particles >21µm		ASTM D7647	>20		20	18
Particles >38µm		ASTM D7647	>4		0	2
Particles >71µm		ASTM D7647	>3		0	0 19/17/13
Oil Cleanliness		ISO 4406 (c)	>18/16/13		18/16/13	
HEAVY METALS		method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185m	<0.1	0	<1	<1
Nickel	ppm	ASTM D5185m	<0.1	0	0	0
Lead	ppm	ASTM D5185m	<0.1	0	0	<1
Vanadium	ppm	ASTM D5185m	<0.1	0	0	0
Iron Calcium	ppm	ASTM D5185m	<0.1	0	0	0
Magnesium	ppm	ASTM D5185m ASTM D5185m	<0.1	<1 0	<1	0
Phosphorus	ppm	ASTM D5165III		<1	0	0
Zinc	ppm	ASTM D5185m	<0.1	0	0	0
ZIIIC	ppm	UO LINI DO LOOIII	<u. i<="" th=""><th>U</th><th>U</th><th>U</th></u.>	U	U	U




FUEL REPORT











Certificate 12367

Laboratory

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 **Sample No.** : DC0036994 Lab Number : 06201099

Unique Number : 11063222

Received Tested Diagnosed

: 05 Jun 2024 : 13 Jun 2024

: 13 Jun 2024 - Doug Bogart Test Package: DF-5 (Additional Tests: API, Cetane, Fuel, PrtCount, Screen)

KELLY GENERATOR & EQUIPMENT INC 1955 DALE LN OWINGS, MD US 20736

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (410)257-5225 F: (410)257-5227

Contact: LESLIE SNURR

LSNURR@KGE.COM

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) Report Id: KELOWI [WUSCAR] 06201099 (Generated: 06/15/2024 06:27:51) Rev: 1

Contact/Location: LESLIE SNURR - KELOWI