

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER 1834118 (S/N 1250)

Component Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- QTS)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sample Number Sample Date Machine Age Oil Age		method	limit/base	current	history1	history2
Machine Age Oil Age		Client Info		KCPA013377		
Oil Age		Client Info		20 May 2024		
-	hrs	Client Info		66846		
	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	0		
Titanium		ASTM D5185m	>3	0		
Silver	ppm		>3	-		
	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm		>50	9		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	90	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	100	<1		
Calcium	ppm	ASTM D5185m	0	0		
Phosphorus	ppm	ASTM D5185m	0	2		
Zinc	ppm	ASTM D5185m	0	0		
Sulfur	ppm	ASTM D5185m	23500	16880		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	0		
Water	%	ASTM D6304	>0.05	0.006		
ppm Water	ppm	ASTM D6304	>500	70		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Dortiolog . 1.m		ASTM D7647		118794		
Panicies >4µm		ASTM D7647	>1300	<u> </u>		
Particles >4µm Particles >6µm		ASTM D7647	>80	10628		
Particles >6µm				A 3664		
Particles >6µm Particles >14µm		ASTIVI D7647				
Particles >6μm Particles >14μm Particles >21μm		ASTM D7647 ASTM D7647	>4	▲ 234		
Particles >6μm Particles >14μm Particles >21μm Particles >38μm		ASTM D7647	>4	<mark>/</mark> 234		
Particles >6μm Particles >14μm Particles >21μm			>4			
Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness		ASTM D7647 ASTM D7647	>4 >3 >/17/13	▲ 234 ▲ 14		
Particles >6μm Particles >14μm Particles >21μm Particles >38μm Particles >71μm	ATION mg KOH/g	ASTM D7647 ASTM D7647 ISO 4406 (c)	>4 >3 >/17/13 limit/base	 234 14 24/23/21 		



A Particle Trend

Water (KF)

Abnormal

Acid Number

Water (KF)

Abnormal nl Mav20/24

Abnormal

Viscosity @ 40°C

Mav20/7

1.20 (B/H0.90 KOH/8) E0.72 - ag 0.48 - Pio 0.24 0.00 Aav20/24

12000 10000 Severe

> 60 Sever 55

() 50 () 50 15 45 Base Abnormal 40 Severe 35 May20/24

.

120k

number of particles (1 ml) 09 80% 09 80%


0k Mav20/24

12000

Built for a lifetime."

4μm 6μm

-14µm



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
0/24	Appearance	scalar	*Visual	NORML	NORML		
May20/24	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.05	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	45	47.1		
	SAMPLE IMAGE		method	limit/base		history1	history?
	SAMPLE IMAGE	-5	method	limit/base	current	nistory i	history2
4							
May20/24	Color					no image	no image
W							
				/			
	Bottom					no image	no image
	GRAPHS						-
	Ferrous Alloys				Particle Count		
	Ferrous Alloys			491,520:	Particle Count		I ²¹
	Ferrous Alloys				Particle Count		2
V-UC	Ferrous Alloys			491,520	Particle Count		
PC-VC-VV	Ferrous Alloys			491,520	Particle Count		21 -2: -2:
SCUC-TH	Ferrous Alloys			491,520 122,880 30,720 7,680	Particle Count		-2:
acuc	Ferrous Alloys			491,520 122,880 30,720 7,680	Particle Count		-2:
accertain accert	Ferrous Alloys			491,520 122,880 30,720 7,680	Particle Count		-2:
PC-UC-FR	Ferrous Alloys	als		491,520 122,880 30,720 7,680	Particle Count	,	-2:
ACCO-AA	Ferrous Alloys	als		491,520 122,880 30,720 7,680	Particle Count		-2:
st-uc-ret	Ferrous Alloys	als		491,520 122,880 30,720 7,680 100 100 100 100 100 100 100 100 100 1	Particle Count		-21
FULL FR	Ferrous Alloys	als		491,520 122,880 30,720 7,680	Particle Count		-2:
VCUC-PY	Ferrous Alloys	als		491,520 122,880 30,720 7,680 120,000 100,0000 100,0000 100,0000 100,00000000			-2:
PUUC-19	Ferrous Alloys	als		491,520 122,880 30,720 7,680 7,90 7,90 7,90 7,90 7,90 7,90 7,90 7,9	Particle Count		-22
ACUC-M	Ferrous Alloys	als		491,520 122,880 30,720 7,680 7,90 7,90 7,90 7,90 7,90 7,90 7,90 7,9			-2
ACAC_A	Ferrous Alloys			491,520 122,880 30,720 7,680 120,000 100,0000 100,0000 100,0000 100,00000000	Bbreenal d 6j4	14μ 21μ	-22
	Ferrous Alloys			491,520 122,880 30,720 7,680 42002/eW 480 120 480 120 30 480 120 480 120 480 120 480 120 480 480 480 480 480 480 480 48	Boreemal		-2 -2 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1
	Ferrous Alloys			491,520 122,880 30,720 7,680 42007/eW 480 1,920 480 120 300 480 120 300 480 120 120 480 120 120 120 120 120 120 120 12	Bbreenal d 6j4		-2 -2 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1
MODA	Ferrous Alloys			491,520 122,880 30,720 7,680 42007/eW 480 1,920 480 120 300 480 120 300 480 120 120 480 120 120 120 120 120 120 120 12	Boreemal 6/4 Acid Number		-2 -2 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1
	Ferrous Alloys			491,520 122,880 30,720 7,680 42007/eW 480 1,920 480 120 300 480 120 300 480 120 120 480 120 120 120 120 120 120 120 12	Boreemal 6/4 Acid Number		-2 -2 -11 -11 -11 -11 -11 -11 -11 -11 -1
	Ferrous Alloys			491,520 122,880 30,720 7,680 42007/eW 480 1,920 480 120 300 480 120 300 480 120 120 480 120 120 120 120 120 120 120 12	Boreemal 6/4 Acid Number		-22 -22 -16 -16 -16 -16 -16 -16 -16 -16 -16 -16
VUUCFT	Ferrous Alloys			491,520 122,880 30,720 7,660 42002/eW 480 120 120 120 480 120 30 120 480 120 120 480 120 120 120 120 120 120 120 12	Boreemal Acid Number		-22 -22 -16 -16 -16 -16 -16 -16 -16 -16 -16 -16
acron-e4	Ferrous Alloys			491,520 122,880 30,720 7,680 42007/eW 480 1,920 480 120 300 480 120 300 480 120 120 480 120 120 120 120 120 120 120 12	Boreemal 6/4 Acid Number		-2 -2 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1 -1

Contact/Location: JOHNNY KELDSEN - WATSAL