


OIL ANALYSIS REPORT

[73558974] **KAESER 4738382**

Component Compressor

KAESER SIGMA (OEM) M-460 (--- QTS)



DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. Elemental level of silicon (Si) above normal.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017870	KCPA011346	KCPA011354
Sample Date		Client Info		29 May 2024	22 Nov 2023	20 Nov 2023
Machine Age	hrs	Client Info		63287	58734	58734
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Sample Status				ABNORMAL	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	4	10	7
Tin	ppm		>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	2	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	100	7	0	0
Calcium	ppm	ASTM D5185m	0	0	0	0
Phosphorus	ppm	ASTM D5185m	0	2	2	0
Zinc	ppm	ASTM D5185m	0	9	0	8
Sulfur	ppm	ASTM D5185m	23500	20542	18915	18538
CONTAMINANTS	1	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	^ 26	<1	0
Sodium	ppm	ASTM D5185m		3	<1	1
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.05	0.003	0.008	0.037
ppm Water	ppm	ASTM D6304	>500	33	81	370
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		9458	3200	
Particles >6µm		ASTM D7647	>1300	△ 3730	1102	
Particles >14µm		ASTM D7647	>80	<u>^</u> 204	90	
Particles >21µm		ASTM D7647	>20	<u>^</u> 52	2 4	
Particles >38μm		ASTM D7647	>4	2	1	
Particles >71μm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 20/19/15	19/17/14	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.36	0.40	0.35



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

Lab Number : 06202075

: KCPA017870 Unique Number : 11069536

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 06 Jun 2024 **Tested** : 11 Jun 2024 : 11 Jun 2024 - Jonathan Hester

Diagnosed Test Package : IND 2 (Additional Tests: KF, PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369. st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

ZERO WASTE ENERGY 685 LOS ESTEROS RD

SAN JOSE, CA US 95134 Contact: A. BARRAZA

abarraza@zwedc.com T:

Report Id: ZERSANCA [WUSCAR] 06202075 (Generated: 06/11/2024 12:46:15) Rev: 1

F: