

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

ELLIOT COMPRESSOR 2 UNIFI (S/N B3EV2E087-3)

Component Compressor

DIAMOND BLUE (--- GAL)

D	ΙΔ		NI		S	15
\boldsymbol{L}	$I \cap$	u	N	v	${\boldsymbol{\circ}}$	\mathbf{I}

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

MPC (Membrane Patch Colorimetry) test indicates acceptable levels of varnish present. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Marzuzz Aug	J2UZZ JanZUZ3 NIBYZUZ3	Aug2023 Nov2023 Jan2024 Jan20	24 Jun2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0903371	WC0903379	WC0886221
Sample Date		Client Info		04 Jun 2024	29 Jan 2024	15 Jan 2024
Machine Age	hrs	Client Info		76039	72998	72707
Oil Age	hrs	Client Info		20439	26275	14062
Oil Changed		Client Info		Changed	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>25	0	<1	<1
Lead	ppm	ASTM D5185m	>25	0	2	0
Copper	ppm	ASTM D5185m	>50	0	2	<1
Tin	ppm	ASTM D5185m	>15	<1	2	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		372	364	348
Molybdenum	ppm	ASTM D5185m		0	<1	0
Manganese	ppm	ASTM D5185m		0	2	0
Magnesium	ppm	ASTM D5185m		1	2	<1
Calcium	ppm	ASTM D5185m		<1	2	1
Phosphorus	ppm	ASTM D5185m		16	19	17
Zinc	ppm	ASTM D5185m		6	<1	0
Sulfur	ppm	ASTM D5185m		190	177	190
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	1
Sodium	ppm	ASTM D5185m		5	8	6
Potassium	ppm	ASTM D5185m	>20	0	4	2
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.25	0.18	0.22
MDON TIPE	0 1	A O.T. A D.70 40	4.5		0	


MPC Varnish Potential Scale ASTM D7843 >15 6



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID FROFE	INTIES	method		HISTORY	HISTORYZ
Visc @ 40°C	cSt	ASTM D445	27.8	28.0	27.9

SAMPLE IMAGES	method				history2
---------------	--------	--	--	--	----------


Color





MPC




GRAPHS













Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: WC0903371 Lab Number : 06202875 Unique Number : 11070336

Received **Tested** Diagnosed

: 07 Jun 2024 : 14 Jun 2024

: 14 Jun 2024 - Doug Bogart

FS-COMPRESSION CO, LLC 203 AERO COURT GREENSBORO, NC US 27409

Contact: Dallas Burcham

F: (336)605-9844

dallas.burcham@fs-compression.com T: (336)605-9622

Certificate 12367

Test Package : IND 2 (Additional Tests: MPC) To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: AIRGREWC [WUSCAR] 06202875 (Generated: 06/14/2024 14:55:43) Rev: 1

Contact/Location: Dallas Burcham - AIRGREWC





Report Id: AIRGREWC [WUSCAR] 06202875 (Generated: 06/14/2024 14:55:46) Rev: 1

This page left intentionally blank