OIL ANALYSIS REPORT

Sample Rating Trend

ISO

Machine Id
[] Oil room tote 25
Component
Bulk Fluid Tank
Fluid
TURBINE OIL ISO 100 (--- GAL)

DIAGNOSIS

Recommendation
No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear
All component wear rates are normal.

Contamination
There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition
The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		**RP0042856**	---	---
Sample Date		Client Info		**05 Jun 2024**	---	---
Machine Age	hrs	Client Info		**0**	---	---
Oil Age	hrs	Client Info		**0**	---	---
Oil Changed		Client Info		**Not Changd**	---	---
Sample Status				**ATTENTION**	---	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m		**0**	---	---
Chromium	ppm	ASTM D5185m		**0**	---	---
Nickel	ppm	ASTM D5185m		**0**	---	---
Titanium	ppm	ASTM D5185m		**0**	---	---
Silver	ppm	ASTM D5185m		**0**	---	---
Aluminum	ppm	ASTM D5185m		**0**	---	---
Lead	ppm	ASTM D5185m		**0**	---	---
Copper	ppm	ASTM D5185m		**0**	---	---
Tin	ppm	ASTM D5185m		**<1**	---	---
Vanadium	ppm	ASTM D5185m		**0**	---	---
Cadmium	ppm	ASTM D5185m		**0**	---	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	**0**	---	---
Barium	ppm	ASTM D5185m	5	**1**	---	---
Molybdenum	ppm	ASTM D5185m	5	**0**	---	---
Manganese	ppm	ASTM D5185m		**<1**	---	---
Magnesium	ppm	ASTM D5185m	5	**4**	---	---
Calcium	ppm	ASTM D5185m	10	**20**	---	---
Phosphorus	ppm	ASTM D5185m	275	**42**	---	---
Zinc	ppm	ASTM D5185m	7	**24**	---	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		**<1**	---	---
Sodium	ppm	ASTM D5185m		**1**	---	---
Potassium	ppm	ASTM D5185m	>20	**2**	---	---
Water	%	ASTM D6304		**0.00**	---	---
ppm Water	ppm	ASTM D6304		**0**	---	---

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	**7273**	---	---
Particles >6µm		ASTM D7647	>1300	**1270**	---	---
Particles >14µm		ASTM D7647	>160	**18**	---	---
Particles >21µm		ASTM D7647	>40	**4**	---	---
Particles >38µm		ASTM D7647	>10	**1**	---	---
Particles >71µm		ASTM D7647	>3	**1**	---	---
Oil Cleanliness		ISO 4406 (c)	>19/17/14	**20/17/11**	---	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.13	**0.088**	---	---

OIL ANALYSIS REPORT

Particle Trend



Water (KF)



Viscosity @ 100°C



Water (KF)



Viscosity @ 100°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	**NONE**	---	---
Yellow Metal	scalar	*Visual	NONE	**NONE**	---	---
Precipitate	scalar	*Visual	NONE	**NONE**	---	---
Silt	scalar	*Visual	NONE	**NONE**	---	---
Debris	scalar	*Visual	NONE	**NONE**	---	---
Sand/Dirt	scalar	*Visual	NONE	**NONE**	---	---
Appearance	scalar	*Visual	NORML	**NORML**	---	---
Odor	scalar	*Visual	NORML	**NORML**	---	---
Emulsified Water	scalar	*Visual		**NEG**	---	---
Free Water	scalar	*Visual		**NEG**	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	100	**90.93**	---	---
Visc @ 100°C	cSt	ASTM D445	11.2	**11.04**	---	---
Viscosity Index (VI)	Scale	ASTM D2270	97	**106**	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				*no image*	*no image*
Bottom				*no image*	*no image*

GRAPHS

Ferrous Alloys



Non-ferrous Metals

Viscosity @ 40°C



Particle Count



Acid Number



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RP0042856 **Received** : 07 Jun 2024
Lab Number : 06203197 **Tested** : 12 Jun 2024
Unique Number : 11070658 **Diagnosed** : 12 Jun 2024 - Angela Borella
Test Package : IND 2 (Additional Tests: KV100, PrtCount, VI)

Certificate L2367

To discuss this sample report, contact Customer Service at 1-800-237-1369.
** - Denotes test methods that are outside of the ISO 17025 scope of accreditation.*
Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CALUMET
3333 MIDWAY AVENUE
SHREVEPORT, LA
US 71109
Contact: NICHOLAS LESAGE
nicholas.lesage@clmt.com
T:
F:

Report Id: CALSHR [WUSCAR] 06203197 (Generated: 06/12/2024 08:41:17) Rev: 1

Submitted By: CODY COMPTON