


# **OIL ANALYSIS REPORT**

Area
S&S FOODS

# HC-3 - SS FOODS (S/N M908-180-A)

**Refrigeration Compressor** 

FRICK COMPRESSOR OIL #11 (100 GAL)





### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2015 Jul2	017 Apr2020 Dec2020 Apr2	021 Oct2021 May2022 Jun2023 Sep2	023 May2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP0012460	USP250280	USP250806
Sample Date		Client Info		23 May 2024	06 Sep 2023	08 Jun 2023
Machine Age	hrs	Client Info		10846	5078	2917
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	0	0	0
Chromium	ppm	ASTM D5185m	>2	<1	<1	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>3	0	<1	0
Lead	ppm	ASTM D5185m	>2	0	0	0
Copper	ppm	ASTM D5185m	>8	<1	0	0
Tin	ppm	ASTM D5185m	>4	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		0	0	<1
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		0	0	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	0
Sodium	ppm	ASTM D5185m		0	1	0
Potassium	ppm	ASTM D5185m	>20	1	3	0
Water	%	ASTM D6304	>0.01	0.001	0.003	0.002
ppm Water	ppm	ASTM D6304	>100	2	27.0	17.0
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	3339	1281	4965
Particles >6µm		ASTM D7647	>2500	473	192	732
Particles >14μm		ASTM D7647	>320	18	15	29
Particles >21µm		ASTM D7647	>80	2	2	6
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	19/16/11	17/15/11	19/17/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974		0.013	0.015	0.014



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No. Lab Number

Unique Number : 11070884 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : USP0012460 : 06203423

Received

**Tested** : 11 Jun 2024 Diagnosed : 11 Jun 2024 - Doug Bogart

: 07 Jun 2024

To discuss this sample report, contact Customer Service at 1-800-237-1369.  $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (714)895-3488 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (714)895-5125

Report Id: RACGAR [WUSCAR] 06203423 (Generated: 06/11/2024 20:35:05) Rev: 1

Contact/Location: TODD CARTER - RACGAR

**RACE ENGINEERING CORP** 

GARDEN GROVE, CA

tcrace@verizon.net

Contact: TODD CARTER

12871 WESTERN AVE, SUITE E

US 92841