


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER ASD 40T 5810272 (S/N 1226)

Component Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jul2017	Apr2018 Feb2020	Sep2021 Dec2022	May2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA016680	KCPA002293	KCP47676D
Sample Date		Client Info		30 May 2024	28 Jun 2023	07 Dec 2022
Machine Age	hrs	Client Info		47945	41161	39404
Oil Age	hrs	Client Info		0	0	2841
Oil Changed		Client Info		Changed	N/A	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	6
Chromium	ppm	ASTM D5185m	>10	0	0	<1
Nickel	ppm	ASTM D5185m	>3	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	<1	3
Lead	ppm	ASTM D5185m	>10	0	0	2
Copper	ppm	ASTM D5185m	>50	9	23	7
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	90	8	5	18
Calcium	ppm	ASTM D5185m	2	0	0	<1
Phosphorus	ppm	ASTM D5185m		2	9	22
Zinc	ppm	ASTM D5185m		35	4	11
Sulfur	ppm	ASTM D5185m		18202	19986	12166
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1
Sodium	ppm	ASTM D5185m		10	9	10
Potassium	ppm	ASTM D5185m	>20	1	3	20
Water	%	ASTM D6304	>0.05	0.011	0.019	0.024
ppm Water	ppm	ASTM D6304	>500	118	192.2	242.3
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		4163		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14μm		ASTM D7647	>80	<u>^</u> 231		
Particles >21μm		ASTM D7647	>20	<u>^</u> 71		
Particles >38μm		ASTM D7647	>4	<u>^</u> 5		
Particles >71μm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u> </u>		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
				Current	1	



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

Lab Number

: KCPA016680 : 06205443 Unique Number : 11072904

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 10 Jun 2024 **Tested** : 12 Jun 2024

: 13 Jun 2024 - Don Baldridge Diagnosed Test Package : IND 2 (Additional Tests: KF, PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) **EUCLID CHEMICAL**

3361 N HWY 27 LAFAYETTE, GA US 30728

Contact: J. MESSER jmesser@euclidchemical.com

T:

Report Id: EUCLAFGA [WUSCAR] 06205443 (Generated: 06/14/2024 07:22:15) Rev: 1

Contact/Location: J. MESSER - EUCLAFGA

F: