




OIL ANALYSIS REPORT

Sample Rating Trend



WATER



Machine Id
PLANT 5 PUMP D
 Component
Vacuum Pump
 Fluid
 {not provided} (--- GAL)

DIAGNOSIS

Recommendation

We advise that you perform a filter service and use off-line filtration to improve the cleanliness of the system fluid. Resample at the next service interval to monitor. There is too much water present in this sample to perform a particle count.

Wear

All component wear rates are normal.

Contamination

Appearance is milky. There is a high concentration of water present in the oil. The high sodium (Na) level indicates the possible presence of salt water.

Fluid Condition

The AN level is acceptable for this fluid.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		USP0013433	USP0008160	USP0001903
Sample Date	Client Info		09 Jun 2024	27 Mar 2024	22 Sep 2023
Machine Age	hrs	Client Info	0	0	0
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info		N/A	N/A	N/A
Sample Status			ABNORMAL	ABNORMAL	SEVERE

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >20	7	1	4
Chromium	ppm	ASTM D5185m >20	0	<1	0
Nickel	ppm	ASTM D5185m >20	<1	<1	0
Titanium	ppm	ASTM D5185m	0	<1	0
Silver	ppm	ASTM D5185m	0	0	0
Aluminum	ppm	ASTM D5185m >20	0	2	0
Lead	ppm	ASTM D5185m >20	0	<1	0
Copper	ppm	ASTM D5185m >20	0	<1	<1
Tin	ppm	ASTM D5185m >20	<1	1	<1
Vanadium	ppm	ASTM D5185m	0	<1	<1
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0
Barium	ppm	ASTM D5185m	<1	0	0
Molybdenum	ppm	ASTM D5185m	0	<1	0
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m	<1	<1	0
Calcium	ppm	ASTM D5185m	4	3	0
Phosphorus	ppm	ASTM D5185m	36	30	397
Zinc	ppm	ASTM D5185m	33	15	0
Sulfur	ppm	ASTM D5185m	46	23	2014

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >15	<1	2	4
Sodium	ppm	ASTM D5185m	28	0	0
Potassium	ppm	ASTM D5185m >20	3	2	0
Water	%	ASTM D6304 >.1	▲ 0.876	0.003	▲ 0.319
ppm Water	ppm	ASTM D6304 >1000	▲ 8760	39	▲ 3190

FLUID CLEANLINESS


	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>5000	---	▲ 19934	---
Particles >6µm	ASTM D7647	>1300	---	● 2060	---
Particles >14µm	ASTM D7647	>160	---	23	---
Particles >21µm	ASTM D7647	>40	---	6	---
Particles >38µm	ASTM D7647	>10	---	0	---
Particles >71µm	ASTM D7647	>3	---	0	---
Oil Cleanliness	ISO 4406 (c)	>19/17/14	---	▲ 21/18/12	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.13	0.09	0.067




OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	▲ HEAVY
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	● MILKY	NORML	● HAZY
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	▲ 0.2%	NEG	0.2%
Free Water	scalar	*Visual	NEG	NEG	▲ 50.0

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	104	103	103

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : USP0013433 **Received** : 10 Jun 2024
Lab Number : 06205520 **Tested** : 12 Jun 2024
Unique Number : 11072981 **Diagnosed** : 12 Jun 2024 - Doug Bogart
Test Package : IND 2

HILMAR CHEESE
 DALHART, TX
 US
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)