

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

Machine Id **79-107** Component **Rear Right Final Drive** Fluid **TO-4 (--- GAL)** 

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0920965		
Sample Date		Client Info		18 May 2024		
Machine Age	hrs	Client Info		2654		
Oil Age	hrs	Client Info		517		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	572		
Chromium	ppm	ASTM D5185m	>10	6		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	5		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		23		
Barium	ppm	ASTM D5185m		3		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		4		
Magnesium	ppm	ASTM D5185m		3		
Calcium	ppm	ASTM D5185m		<1		
Phosphorus	ppm	ASTM D5185m		630		
Zinc	ppm	ASTM D5185m		12		
Sulfur		ASTM D5185m		20502		
	ppm					
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	16		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	3		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
:00:04) Rev: 1	Journa					atlow - NANKOT



# **OIL ANALYSIS REPORT**



FLUID PROPER	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		86.9		
SAMPLE IMAGI	ES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image
GRAPHS			L			
Ferrous Alloys						
500 - nickel						
400 -						
틆 300 -						
200 -						
100 -						
			54			
May18/24			May18/24			
Non-ferrous Met	als					
9 - copper						
8 tin						
6 - 튼 5 -						
4						
2						
0						
May18/24			May18/24			
Viscosity @ 40°C	2					
130 Abnormal 125						
115-						
110 105 						
ස් 100 95						
90						
80 - <b>Abnormal</b>			-			
May18/24			May18/24 -			
Ma			May			
: WearCheck USA - 5	01 Madis	on Ave., Cary,	NC 27513		NANA LYNDI	EN LOGISTIC
: WC0920965 r : 06205765		eived : 10	Jun 2024 Jun 2024		k	P.O. BOX 57 OTZEBUE, A
r : 11073226			Jun 2024 - Ang	ela Borella		US 9975
e : FLEET t, contact Customer Ser					nanalynde	ct: Mark Tatlo n@lynden.co

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: Mark Tatlow - NANKOT

T: (907)754-5551

F: (800)418-0974

<sup>\* -</sup> Denotes test methods that are outside of the ISO 17025 scope of accreditation.