

### **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

Machine Id

# FRICK RC11 - WAYNE FARM

Refrigeration Compressor

Fluid REFRIG COMP OIL ISO 68 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	<b>NATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0951857		
Sample Date		Client Info		06 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	6		
Chromium	ppm	ASTM D5185m	>2	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>3	2		
Lead	ppm	ASTM D5185m	>2	0		
Copper	ppm	ASTM D5185m	>8	<1		
Tin	ppm	ASTM D5185m	>4	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
	1-1-					
ADDITIVES	T- T-	method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base 5	current 0	history1	history2
					,	
Boron	ppm	ASTM D5185m	5	0		
Boron Barium	ppm ppm	ASTM D5185m ASTM D5185m	5 5	0 0		
Boron Barium Molybdenum	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	5 5	0 0 0		
Boron Barium Molybdenum Manganese	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5	0 0 0		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 5	0 0 0 0 0		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 5 12	0 0 0 0 0	  	  
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 5 12 12	0 0 0 0 0 0 0	   	   
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 12 12 12 12	0 0 0 0 0 0 0 0	    	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 12 12 12 12 12 12 1000	0 0 0 0 0 0 0 0 0 0		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	5 5 5 12 12 12 12 12 1000	0 0 0 0 0 0 0 0 0 0 0 0 0	     history1	     history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m <b>method</b>	5 5 5 12 12 12 12 12 1000	0 0 0 0 0 0 0 0 0 0 0 0 0 2 0 0 0 2 1	     history1 	     history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m <b>method</b> ASTM D5185m	5 5 5 12 12 12 12 12 1000 imit/base >15	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	     history1 	    history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	5 5 5 12 12 12 12 12 12 1000 <b>limit/base</b> >15	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	     history1	     history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Water	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	5 5 5 12 12 12 12 12 1000 <b>limit/base</b> >15 >20 >0.01	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	      history1  	     history2  




## **OIL ANALYSIS REPORT**


VIOLIA







	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Jun6/24	Appearance	scalar	*Visual	NORML	NORML		
٦٢	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.01	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	68	65.3		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Jun6/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta	ls		Jun6.24 - Jun6.24			
	Viscosity @ 40°C				Acid Number		
	(2-0-0) 33 65 60 55 40 40 40 40 40 40 40 40 40 40			(D,HO) Q (D, HO)	Abnormal PCGgun		
	: WearCheck USA - 50 : WC0951857 : 06206604 : 11074065	1 Madiso Rece Teste Diagr	ived : 11 ed : 18		SOUTH		



To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SOUBIR [WUSCAR] 06206604 (Generated: 06/18/2024 16:26:28) Rev: 1

Certificate 12367

Contact/Location: GREGG KING - SOUBIR

Page 2 of 2

gregg@serfco.com

T: (205)322-6587

F: (205)322-6580