

## **OIL ANALYSIS REPORT**

# Sample Rating Trend **NORMAL**

# **ROTO XTEND [420567]** ATLAS COPCO API434833 - METAL COMPONENTS

Component Compressor

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06206712	UCH06106254	
Sample Date		Client Info		20 May 2024	02 Mar 2024	
Machine Age	hrs	Client Info		24630	24215	
Oil Age	hrs	Client Info		415	2800	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>5	<1	<1	
Nickel	ppm	ASTM D5185m		0	<1	
Titanium	ppm	ASTM D5185m		<1	<1	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>15	2	7	
Lead	ppm	ASTM D5185m	>65	<1	1	
Copper	ppm	ASTM D5185m	>65	1	1	
Tin	ppm	ASTM D5185m	>10	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		<1	<1	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m		2	2	
Calcium	ppm	ASTM D5185m		0	0	
Phosphorus	ppm	ASTM D5185m		52	32	
Zinc	ppm	ASTM D5185m		96	15	
Sulfur	ppm	ASTM D5185m		46	<1	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	<1	1	
Sodium	ppm	ASTM D5185m		4	0	
Potassium	ppm	ASTM D5185m	>20	1	<1	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.14	0.16	0.134	





## **OIL ANALYSIS REPORT**




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPERT	IFS	method	limit/base	current	history1	history2
					•	
Visc @ 40°C	cSt	ASTM D445	46	47.3	47.5	
0444515144056						
SAMPLE IMAGES	5	method	limit/base	current	history1	history2
Color		method	limit/base	current	history1	history2 no image
		method	limit/base		history1	
Color		method	limit/base		history1	no image













Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06206712

: UCH06206712 Unique Number : 11074173

Received : 11 Jun 2024 **Tested** : 13 Jun 2024 Diagnosed

: 13 Jun 2024 - Sean Felton

US 07072 Contact: ELVIN DIAZ ediaz@airmaticcompressor.com;canastasio@wearcheckusa.com

**AIRMATIC COMPRESSOR SYSTEMS** 

700 WASHINGTON AVE

CARLSTADT, NJ

T: (800)864-7621

F: (201)342-6241

Test Package : IND 2 Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ELVIN DIAZ - UCAIRCAR