


OIL ANALYSIS REPORT

[1990455] WP04-XF02 (S/N 31990071)

Hydraulic System

MOBIL DTE 25 (--- GAL)





Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

All component wear rates are normal.

Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Augzoto	Marzori Decres	TOUZUZT MOJZUZT MOJZUZT	OUNEOET	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0911573	WC0891452	WC0891446
Sample Date		Client Info		02 Jun 2024	10 May 2024	07 Mar 2024
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ATTENTION	ATTENTION
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	13	13	13
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>20	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>20	0	0	2
Lead	ppm	ASTM D5185m	>20	0	<1	2
Copper	ppm	ASTM D5185m	>20	2	3	2
Tin	ppm	ASTM D5185m	>20	0	1	2
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	<1	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		<1	1	1
Magnesium	ppm	ASTM D5185m		<1	<1	1
Calcium	ppm	ASTM D5185m		78	77	79
Phosphorus	ppm	ASTM D5185m		473	478	496
Zinc	ppm	ASTM D5185m		640	652	650
Sulfur	ppm	ASTM D5185m		6417	6733	6290
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	2	3	3
Sodium	ppm	ASTM D5185m		19	19	19
Potassium	ppm	ASTM D5185m	>20	2	2	4
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	8277	9368	7317
Particles >6µm		ASTM D7647	>1300	<u> </u>	2028	1043
Particles >14μm		ASTM D7647	>160	121	66	61
Particles >21µm		ASTM D7647	>40	20	10	14
Particles >38µm		ASTM D7647	>10	1	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	0 20/18/14	0 20/18/13	0 20/17/13
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
	1/01/					




OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	44.2	48.0	47.6	47.94
SAMPLE IMAGES		method	limit/base	current	history1	history2

GRAPHS				
Ferrous Alloys			Particle Count	
20 iron	^		491,520	Č.
15 - E 10	_		122,880	Ē
E 10 - sanaranan nickel			30,720	
0		lks there be a part of the same of the sam	- 7,680 Phagormal +20	1 20
Aug1/18 Mar4/21 Dec8/23	Feb8/24 - Mar7/24 -	May10/24 .		0 440
Aug Ma	Fet Ma	Mayl	1.920	6:199
Non-ferrous Metals	5		1800 - 18	ISO 4406:1999 Cleanliness Code
10 copper			120-	nlines
E 6 - management lead			30	s Code
4				
Andread and and a second and a	CARL DESCRIPTION OF THE PARTY O	William Control of the last of	8 10	Ä
Aug1/18 Mar4/21 Dec8/23	Feb8/24.	May10/24 -	2	
Aug Ma	Ma Rel	May	$0 + \frac{1}{4\mu} = \frac{1}{6\mu} = \frac{1}{4\mu} = \frac{1}{24\mu} = \frac{1}{38\mu} = \frac{7}{16\mu}$	
Viscosity @ 40°C			Acid Number	
55 Abnormal			(B)1.2	-
50 Abnormal			E 0.7-	-1-
Abnormal			e 0.5 −	
35			(0)1.2 HOX 1.0 EL) 0.7 aq 0.5 UN 0.2 PQ 0.0	
Mar4/21 -	Feb8/24	lay10/24 -	Aug1/18 Mar4/21 Feb8/24 Feb8/24 Iay10/24	Jun2/24
Aug Mar	Feb	May10/24 Jun2/24	Aug1/18 Mar4/21 Dec8/23 Feb8/24 Mar7/24	Jul





Laboratory

Sample No. : WC0911573 Lab Number : 06207071 $\textbf{Unique Number} \quad : 11074532$

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Color

Bottom

Received **Tested**

Diagnosed

: 13 Jun 2024 : 13 Jun 2024 - Wes Davis

: 11 Jun 2024

LEMOORE, CA US 93245 Contact: CHRISTOPHER FOGG

LEPRINO FOODS - LEMOORE EAST

cfogg@leprinofoods.com T: (559)925-7137

Test Package : IND 2 Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F:

490 F ST.