

# **OIL ANALYSIS REPORT**



### Area **COLORADO/443/EG - EXCAVATOR** 20.407L [COLORADO^443^EG - EXCAVATOR] Component Hydraulic System

Fluid MOBIL MOBILTRANS AST 30 (--- GAL)



DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0928708	WC0859726	WC0766224
Sample Date		Client Info		04 Jun 2024	20 Oct 2023	17 Feb 2023
Machine Age	hrs	Client Info		8257	7787	7313
Oil Age	hrs	Client Info		470	0	6106
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	J	method	limit/base	current	historv1	historv2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	6	5	5
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>10	2	1	<1
Lead	ppm	ASTM D5185m	>10	<1	<1	<1
Copper	ppm	ASTM D5185m	>75	5	4	3
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		29	27	29
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		16	17	26
Calcium	ppm	ASTM D5185m		2601	2428	2542
Phosphorus	ppm	ASTM D5185m		935	939	899
Zinc	ppm	ASTM D5185m		1204	1157	1167
Sulfur	ppm	ASTM D5185m		4673	4110	4836
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	5	5
Sodium	ppm	ASTM D5185m		<1	3	2
Potassium	ppm	ASTM D5185m	>20	2	<1	1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		664	659	852
Particles >6µm		ASTM D7647	>2500	74	139	204
Particles >14µm		ASTM D7647	>640	5	12	13
Particles >21µm		ASTM D7647	>160	1	4	3
Particles >38µm		ASTM D7647	>40	0	1	0
Particles >71µm		ASTM D7647	>10	0	1	0
Oil Cleanliness		ISO 4406 (c)	>/18/16	17/13/10	17/14/11	17/15/11
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		1.15	1.05	1.07
:53:45) Bev: 1				Sub	mitted By: BRAN	IDEN JAQUIAS

Report Id: SHEWIC [WUSCAR] 06207729 (Generated: 06/15/2024 08:53:45) Rev: 1

Submitted By: BRANDEN JAQUIA



## **OIL ANALYSIS REPORT**









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	57.6	85.9	83.9	85.5
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color						
Bottom						



- Certificate L2367 Unique Number : 11075190 Test Package : CONST
- To discuss this sample report, contact Customer Service at 1-800-237-1369.
- \* Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SHEWIC [WUSCAR] 06207729 (Generated: 06/15/2024 08:53:45) Rev: 1

Submitted By: BRANDEN JAQUIAS

Page 2 of 2

F: x:

Contact: DOUG KING

doug.king@sherwood.net T: (316)617-3161