

OIL ANALYSIS REPORT

Area S-46 [282691] GARDNER DENVER G/D APEX 25-30A - NORTH CENTRAL STAMP (S/N NOT GIVEN)

Component Compressor

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




Sample Rating Trend



SAMPLE INFORM	/IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0001594		
Sample Date		Client Info		06 Jun 2024		
Machine Age	hrs	Client Info		17368		
Oil Age	hrs	Client Info		4736		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		68		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		1201		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.12		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Jun6/24	Appearance	scalar	*Visual	NORML	NORML			
٦	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	IES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445		47.4			
	SAMPLE IMAGES	5	method	limit/base	current	history1	history2	
Jun6/24	Color				-	• no image	no image	
	Bottom					no image	no image	
	8 6 4 2 0 4 4 2 0 4 4 4 2 0 4 4 4 4 4 4 4 4			Jun6/24				
	Non-ferrous Metals	S		Jun6/24				
	Viscosity @ 40°C			0.15 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.	Acid Numbe	r		
	35			Jun6/24	Jun6/24		Jun6/24	
Centificate 12367 Centificate 12367 O discuss this sample report, - Denotes test methods that	o. : UFD0001594 Received : 12 Jun 2024 per : 06207927 Tested : 14 Jun 2024 ber : 11075388 Diagnosed : 14 Jun 2024 - Wes Davis					FLUID-AIRE DYNAMICS - (MN) 14250 JUDICIAL ROAD BURNSVILLE, MN US 55306 Contact: Service Manager T: 106:2012) F:		

Contact/Location: Service Manager - UCFLUBUR