




# OIL ANALYSIS REPORT

## Sample Rating Trend



ISO



Area

**East Molding**

Machine Id

**518 (S/N 61024486)**

Component

**Hydraulic System**

Fluid

**AW HYDRAULIC OIL ISO 46 (265 GAL)**

### DIAGNOSIS

#### Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil. The water content is negligible.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>RP0043251</b>	RP0035823	RP0029223
Sample Date	Client Info			<b>08 Jun 2024</b>	28 Nov 2023	03 May 2023
Machine Age	hrs	Client Info		<b>0</b>	0	0
Oil Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed	Client Info			<b>N/A</b>	N/A	N/A
Sample Status				<b>ATTENTION</b>	ATTENTION	NORMAL

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<b>4</b>	2	3
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m	>20	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	0
Lead	ppm	ASTM D5185m	>20	<b>6</b>	8	11
Copper	ppm	ASTM D5185m	>20	<b>10</b>	11	11
Tin	ppm	ASTM D5185m	>20	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	<b>0</b>	0	0
Barium	ppm	ASTM D5185m	5	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	5	<b>1</b>	0	1
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m	25	<b>3</b>	1	7
Calcium	ppm	ASTM D5185m	200	<b>56</b>	58	62
Phosphorus	ppm	ASTM D5185m	300	<b>345</b>	355	355
Zinc	ppm	ASTM D5185m	370	<b>391</b>	407	423


CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Sodium	ppm	ASTM D5185m		<b>4</b>	3	0
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	0	2
Water	%	ASTM D6304	>0.05	<b>0.008</b>	0.004	0.003
ppm Water	ppm	ASTM D6304	>500	<b>83</b>	48	26.9

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	<b>6606</b>	5065	519
Particles >6µm		ASTM D7647	>1300	<b>1624</b>	1642	104
Particles >14µm		ASTM D7647	>160	<b>111</b>	159	5
Particles >21µm		ASTM D7647	>40	<b>25</b>	40	1
Particles >38µm		ASTM D7647	>10	<b>1</b>	2	0
Particles >71µm		ASTM D7647	>3	<b>0</b>	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	<b>20/18/14</b>	20/18/14	16/14/10


FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	<b>0.39</b>	0.44	0.37

# OIL ANALYSIS REPORT


## Particle Trend




## Water (KF)




## Acid Number



## Water (KF)



## Viscosity @ 40°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.0	43.8

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color




Bottom




## GRAPHS


### Ferrous Alloys




### Non-ferrous Metals




### Viscosity @ 40°C



### Particle Count



### Acid Number



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : RP0043251  
**Lab Number** : 06208281  
**Unique Number** : 11075742  
**Test Package** : IND 2

**Received** : 12 Jun 2024  
**Tested** : 13 Jun 2024  
**Diagnosed** : 13 Jun 2024 - Wes Davis

**YANFENG AUTOMOTIVE INTERIORS**  
 1600 S. WASHINGTON AVE.  
 HOLLAND, MI  
 US 49423

Contact: JEFF HARRIS  
 jeffrey.harris@yanfeng.com

T: (616)915-4443

F: (616)394-1725

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)