




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
MCI 2045

Component
Diesel Engine

Fluid
PURUS SYNTHETIC BLEND 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0859099	WC0859023	WC0859003
Sample Date	Client Info			21 May 2024	12 Jan 2024	17 Oct 2023
Machine Age	mls	Client Info		383320	344343	325151
Oil Age	mls	Client Info		20000	19000	0
Oil Changed	Client Info			Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	8	23	23
Chromium	ppm	ASTM D5185m	>20	<1	2	<1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>2	0	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	4	3
Lead	ppm	ASTM D5185m	>40	0	0	1
Copper	ppm	ASTM D5185m	>330	0	<1	<1
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		7	73	31
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		59	124	47
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		955	1488	563
Calcium	ppm	ASTM D5185m		1106	1610	1701
Phosphorus	ppm	ASTM D5185m		1014	1558	856
Zinc	ppm	ASTM D5185m		1290	1827	982
Sulfur	ppm	ASTM D5185m		3699	5162	2538





CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6	12	11
Sodium	ppm	ASTM D5185m		<1	5	2
Potassium	ppm	ASTM D5185m	>20	1	2	3

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	0.7	0.8	0.3
Nitration	Abs/cm	*ASTM D7624	>20	8.1	9.0	10.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.4	19.7	23.0

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.7	15.2	23.8
Base Number (BN)	mg KOH/g	ASTM D2896	10	7.4	8.1	8.4







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.3	11.0	13.3

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0859099 **Received** : 12 Jun 2024
Lab Number : 06208308 **Tested** : 14 Jun 2024
Unique Number : 11075769 **Diagnosed** : 14 Jun 2024 - Don Baldrige
Test Package : FLEET (Additional Tests: KV40)

JEFFERSON LINES
 1830 4TH AVE N
 BILLINGS, MT
 US 59101
 Contact: BILLINGS SHOP
 billingsshop@jeffersonlines.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)