

# **OIL ANALYSIS REPORT**

Area ASL-46 [1658] **ATLAS COPCO API536998 - ACCURATE PRECISION PLATING** Component Compressor

### Recommendation

Resample at the next service interval to monitor.

### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

## Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.






SAMPLE INFORM	<b>NATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06208790	UCH05986650	
Sample Date		Client Info		12 Jun 2024	16 Oct 2023	
Machine Age	hrs	Client Info		23971	23272	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	
Chromium	ppm	ASTM D5185m	>5	0	0	
Nickel	ppm	ASTM D5185m		0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>15	0	0	
Lead	ppm	ASTM D5185m	>65	0	0	
Copper	ppm	ASTM D5185m	>65	0	0	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1.5	0	0	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	0.3	0	0	
Magnesium	ppm	ASTM D5185m	0	0	0	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	406	221	275	
Zinc	ppm	ASTM D5185m	0	15	48	
Sulfur	ppm	ASTM D5185m	1283	959	220	
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	0	<1	
Sodium	ppm	ASTM D5185m		1	5	
Potassium	ppm	ASTM D5185m	>20	0	0	
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	0.16	0.165	

Sample Rating Trend



44 Abnormal 42 40 0ct16/23

# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	NONE	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Jun12/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
luul	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.1	NEG	0.2%	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	47.9	45.0	45.6	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
	Color						no image
	Bottom						no image
	Non-ferrous Meta	als		Jun12/24			
	Non-ferrous Meta Non-ferrous Meta Log Log Solution Non-ferrous Meta Log Log Solution Non-ferrous Meta Log Log Solution Log Solu			4722Lunr (0)H0 X0 Mu Jaquer 100 X0 X0 Jaquer 100 X0 Jaquer 100 X0 Jaquer 100 X0 X	20		
	Non-ferrous Meta Non-ferrous Meta lead bead bead viscosity @ 40°C bead			10.5 (6)MOV 0.0 0.0 0.0 0.0 0.0	0 Base		

Report Id: UCAIRDEE [WUSCAR] 06208790 (Generated: 06/14/2024 13:31:20) Rev: 1

Contact/Location: Brandon Schmill - UCAIRDEE