


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

77-PC-24 (S/N 60A)

Component Hydraulic System

Skydrol (--- LTR)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

A Waar

The copper level is abnormal. All other component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service. Chlorine 263 ppm.

				Jun 2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0938110		
Sample Date		Client Info		08 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	<1		
Copper	ppm	ASTM D5185m	>20	<u>^ 129</u>		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m	720	0		
Cadmium	ppm	ASTM D5185m		2		
	ррііі			-		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m	110	3		
Phosphorus	ppm	ASTM D5185m	37	26705		
Zinc	ppm	ASTM D5185m		43		
Sulfur	ppm	ASTM D5185m	220	2131		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	23		
Chlorine Content	ppm	ASTM D5185m		263		
Water	%	ASTM D6304	>0.750	NEG		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>5000	1638		
Particles >6µm		ASTM D7647	>1300	375		
Particles >14μm		ASTM D7647	>160	11		
Particles >21µm		ASTM D7647	>40	2		
Particles >38μm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/16/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.04	0.436		



OIL ANALYSIS REPORT





Certificate 12367

Laboratory Sample No.

Lab Number : 06209091

: WC0938110 Unique Number : 11076552

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 13 Jun 2024 **Tested** : 19 Jun 2024

Diagnosed : 19 Jun 2024 - Jonathan Hester Test Package: PLANT (Additional Tests: A-FERR, CHLORINEXRF)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

WOODWARD

25200 W RYE CANYON RD SANTA CLARITA, CA US 91355

Contact: REYNARD GOLDMAN reynard.goldman@woodward.com T: (661)702-5991