

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL





[W02008366] VOLVO A30G 340101

Hydraulic System
Fluid
{not provided} (50 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample. (Customer Sample Comment: W02008366)

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

L)				Jun2024		
•						
SAMPLE INFORM	NOITAN	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0002450		
Sample Date		Client Info		11 Jun 2024		
Machine Age	hrs	Client Info		12563		
Oil Age	hrs	Client Info		2000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	6		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	2		
Copper	ppm	ASTM D5185m	>150	4		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		98		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		3		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		46		
Calcium	ppm	ASTM D5185m		2792		
Phosphorus	ppm					
Zinc	ppiii	ASTM D5185m		921		
ZITIC	ppm	ASTM D5185m ASTM D5185m		-		
Sulfur	• • • • • • • • • • • • • • • • • • • •			921		
-	ppm ppm	ASTM D5185m	limit/base	921 1206		
Sulfur	ppm ppm	ASTM D5185m ASTM D5185m	limit/base	921 1206 6916	 	
Sulfur CONTAMINANTS	ppm ppm	ASTM D5185m ASTM D5185m method		921 1206 6916 current	 history1	 history2
Sulfur CONTAMINANTS Silicon	ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m		921 1206 6916 current	 history1	 history2
Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m	>20	921 1206 6916 current 15	 history1 	 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	>20 >20	921 1206 6916 current 15 4	 history1 	 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method	>20 >20 limit/base	921 1206 6916 current 15 4 2	 history1 history1	history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647	>20 >20 limit/base	921 1206 6916 current 15 4 2 current 2399	history1 history1 history1	history2 history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647 ASTM D7647	>20 >20 limit/base >5000	921 1206 6916 current 15 4 2 current 2399 548	history1 history1 history1	history2 history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160	921 1206 6916 current 15 4 2 current 2399 548 26	history1 history1 history1	history2 history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160 >40	921 1206 6916 current 15 4 2 current 2399 548 26 3	history1 history1 history1	history2 history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >21µm Particles >38µm	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >160 >40 >10	921 1206 6916 current 15 4 2 current 2399 548 26 3 0	history1 history1 history1	history2 history2 history2
Sulfur CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >21µm Particles >38µm Particles >71µm	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647	>20 simit/base	921 1206 6916 current 15 4 2 current 2399 548 26 3 0 0	history1 history1	history2 history2

Submitted By: DARRELL ANDES



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No. Lab Number : 06209169

: ML0002450 Unique Number : 11076630 Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 13 Jun 2024 **Tested** : 16 Jun 2024

Diagnosed : 16 Jun 2024 - Doug Bogart

To discuss this sample report, contact Customer Service at 1-800-237-1369.

US 20153 Contact: SERVICE MANAGER jimmy_elswick@wahazel.com T: (703)378-8300

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

WILLIAM HAZEL

CHANTILLY, VA

PO BOX 600