


OIL ANALYSIS REPORT

Area

CHEMLUBE 634 [1677526] L9-ML-BMC-BICO-SPMP - PFNONWOVENS

Component Gearbox



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Insufficient sample was received to conduct all the routine laboratory tests.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The condition of the oil is acceptable for the time in service.


0.4.4.B. E. IN.E.O.B.						
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06209288	UCH05863641	
Sample Date		Client Info		21 May 2024	11 Apr 2023	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	1	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	74	65	
Chromium	ppm	ASTM D5185m	>15	<1	<1	
Nickel	ppm	ASTM D5185m	>15	0	0	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	2	0	
Lead	ppm	ASTM D5185m	>100	<1	0	
Copper	ppm	ASTM D5185m	>200	<1	<1	
Tin	ppm	ASTM D5185m	>25	<1	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0.9	0	<1	
Barium	ppm	ASTM D5185m	0.1	0	0	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	0.2	<1	<1	
Magnesium	ppm	ASTM D5185m	0.5	<1	0	
Calcium	ppm	ASTM D5185m	0	0	8	
Phosphorus	ppm	ASTM D5185m	1390	288	281	
Zinc	ppm	ASTM D5185m	0	12	2	
Sulfur	ppm	ASTM D5185m	291	10757	10309	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	5	3	
Sodium	ppm	ASTM D5185m		0	1	
Potassium	ppm	ASTM D5185m	>20	1	0	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.124		0.49	




OIL ANALYSIS REPORT




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPERT	IES	method	limit/base	current	history1	history2
FLUID PROPERT Visc @ 40°C	IES cSt	method ASTM D445	limit/base 453.9	current 459	history1 464	history2
	cSt					history2 history2
Visc @ 40°C	cSt	ASTM D445	453.9	459	464	













Certificate 12367

Laboratory Sample No.

Lab Number : 06209288 Unique Number : 11076749

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCH06209288

Test Package : IND 2

Received : 13 Jun 2024 **Tested**

: 17 Jun 2024 Diagnosed : 17 Jun 2024 - Sean Felton

CORROSION PRODUCTS & EQUIPMENT 940 POINTVIEW AVE

EPHRATA, PA US 17522

Contact: RYAN HUNGARTER rhungarter@corrosion-products.com T: (717)961-1998

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCPROWES [WUSCAR] 06209288 (Generated: 06/17/2024 16:02:27) Rev: 1

Contact/Location: RYAN HUNGARTER - UCPROWES