

# **OIL ANALYSIS REPORT**

Sample Rating Trend



## Area [W02008367] Wachine Io VOLVO L70G 3009

Transmission Fluid {not provided} (5 GAL)

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample. ( Customer Sample Comment: W02008367 )

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.


#### Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0002498		
Sample Date		Client Info		11 Jun 2024		
Machine Age	hrs	Client Info		15116		
Oil Age	hrs	Client Info		2000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	NI.	method	limit/base	ourropt	history1	history?
Water	N	WC Method		current	history1	history2
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	28		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>30	3		
Lead	ppm	ASTM D5185m	>50	0		
Copper	ppm	ASTM D5185m	>50	13		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		78		
Barium	ppm	ASTM D5185m		0		
Volybdenum	ppm	ASTM D5185m		1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium		ASTM D5185m		31		
Calcium	ppm	ASTM D5185m		224		
	ppm					
Phosphorus	ppm	ASTM D5185m		267		
Zinc	ppm	ASTM D5185m		86		
Sulfur	ppm	ASTM D5185m		1908		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	6		
Sodium	ppm	ASTM D5185m		8		
Potassium	ppm	ASTM D5185m	>20	0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual	2 V.L	NEG		
10:02) Rev: 1	Scaidi	visual			ubmitted By: DA	



# **OIL ANALYSIS REPORT**



C	FLUID PROPERTIES		method limit/base		current	history1	history2		
	Visc @ 40°C	cSt	ASTM D445		24.7				
	SAMPLE IMAGE	ES	method	limit/base	current	history1	history2		
	Color				no image	no image	no image		
- 24									
Jun11/24									
	Bottom				no image	no image	no image		
	GRAPHS								
	Ferrous Alloys								
	<sup>30</sup>			1					
	25 - chromium								
	20 -								
	튭 15 -								
	10								
	5-								
	0								
	Jun 1 1/24			Jun 11/24					
	Non-ferrous Meta	als		-					
	14 12								
	10								
	8								
	Edd 6-								
	4								
	2								
	1/24		********	1/24					
	Jun11/24			Jun11/24					
	Viscosity @ 40°C								
	Abnormal 100 -								
	90 Abnormal 80 -								
	(고) 70 - 중 60 -								
	50 <b>-</b> 40 <b>-</b>								
	30-								
	20 + 72/11 unr			11/24					
	L nu L			Jun11/24					
Laboratory	: WearCheck USA - 5	01 Madier	on Ave Carv	NC 27512		10/1	LLIAM HAZEL		
Sample No.	: ML0002498		PO BOX 600						
Lab Number Unique Number		Teste Diagi		Jun 2024 Jun 2024 - Dor	n Baldridge	C	HANTILLY, VA US 20153		
Certificate L2367 Test Package							Contact: SERVICE MANAGER jimmy_elswick@wahazel.com		
* - Denotes test methods that	are outside of the ISO	17025 sco	ope of accred	itation.		T:	(703)378-8300		
Statements of conformity to sp	pecifications are based	on the sir	nple acceptar	nce decision	rule (JCGM 1	06:2012)	F:		

Submitted By: DARRELL ANDES

Page 2 of 2