

OIL ANALYSIS REPORT



Machine Id **2350** Component **Diesel Engine** Fluid **DIESEL ENGINE OIL SAE 5W30 (--- GAL)**

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

			1			
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		HRE0000212		
Sample Date		Client Info		08 May 2024		
Machine Age	mls	Client Info		111792		
Oil Age	mls	Client Info		50000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	70		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	35		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	12		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		2		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	18		
Barium	ppm	ASTM D5185m	10	<1		
Molybdenum	ppm	ASTM D5185m	100	33		
Manganese	ppm	ASTM D5185m		3		
Magnesium	ppm	ASTM D5185m	450	979		
Calcium	ppm	ASTM D5185m	3000	1232		
Phosphorus	ppm	ASTM D5185m	1150	910		
Zinc	ppm	ASTM D5185m	1350	1104		
Sulfur	ppm	ASTM D5185m	4250	3413		
CONTAMINANTS		method				
	>	method	IIIIII/Dase	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	current 23	history1	
Silicon Sodium						
Silicon Sodium	ppm	ASTM D5185m		23		
Silicon Sodium	ppm ppm	ASTM D5185m ASTM D5185m	>25	23 8		
Silicon Sodium Potassium INFRA-RED	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>25 >20	23 8 99		
Silicon Sodium Potassium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method	>25 >20 limit/base	23 8 99 current	 history1	 history2
Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844	>25 >20 limit/base >3	23 8 99 current 0.6	 history1	 history2
Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	>25 >20 limit/base >3 >20	23 8 99 current 0.6 13.2	 history1 	 history2
Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415	>25 >20 limit/base >3 >20 >30	23 8 99 current 0.6 13.2 28.9	 history1 	 history2



OIL ANALYSIS REPORT



Contact/Location: MAINTENANCE ? - MABEDE