


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id **SIZING 1** 

Top Hydraulic System

**FUCHS RENOLIN UNISYN CLP 220 (--- GAI** 

## **DIAGNOSIS**

#### Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. Please note that this is a corrected copy.

#### Wear

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.


#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

		İ				\
L)				Jun2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		FCH0000242		
Sample Date		Client Info		13 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed	1110	Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	0		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		7		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		13		
Phosphorus	ppm	ASTM D5185m		202		
Zinc	ppm	ASTM D5185m		10		
Sulfur	ppm	ASTM D5185m		6285		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	0		
Water	%	ASTM D6304	>0.05	NEG		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>160	<b>3215</b>		
Particles >6µm		ASTM D7647		<b>1256</b>		
Particles >14µm		ASTM D7647		<b>^</b> 54		
Particles >21µm		ASTM D7647	>3	3		
Particles >38µm		ASTM D7647	>3	1		
Particles >71μm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>14/6/4	<b>19/17/13</b>		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.6	0.58		



# **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

Lab Number : 06210073 Unique Number : 11082937

Test Package : PLANT

: FCH0000242

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received : 14 Jun 2024 **Tested** : 27 Jun 2024 Diagnosed

: 27 Jun 2024 - Doug Bogart

**ATLAS TUBE** 5661 E STATE STREET HWY 137 BLYTHEVILLE, AR

US 72315

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: