

OIL ANALYSIS REPORT

Sample Rating Trend



Area FGG 1150 Machine Id SC 2 - BUFFALO WATER Gearbox

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UCH06210085 | | |
| Sample Date | | Client Info | | 13 Jun 2024 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | ABNORMAL | | |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.2 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >200 | 0 | | |
| Chromium | ppm | ASTM D5185m | >15 | 0 | | |
| Nickel | ppm | ASTM D5185m | >15 | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 0 | | |
| Lead | ppm | ASTM D5185m | >100 | 0 | | |
| Copper | ppm | ASTM D5185m | >200 | 0 | | |
| Tin | ppm | ASTM D5185m | >25 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 0 | 0 | | |
| Barium | ppm | ASTM D5185m | 0 | 0 | | |
| Molybdenum | ppm | ASTM D5185m | 0.1 | 0 | | |
| Manganese | ppm | ASTM D5185m | 0.2 | 0 | | |
| Magnesium | ppm | ASTM D5185m | 1.8 | 0 | | |
| Calcium | ppm | ASTM D5185m | 0 | 1 | | |
| Phosphorus | ppm | ASTM D5185m | 573 | 480 | | |
| Zinc | ppm | ASTM D5185m | 0 | 4 | | |
| Sulfur | ppm | ASTM D5185m | 576 | 796 | | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >50 | 3 | | |
| Sodium | ppm | ASTM D5185m | | 0 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 0.425 | 0.12 | | |




OIL ANALYSIS REPORT

method

limit/base

current

VISUAL



| White Metal | scalar | *Visual | NONE | NONE | | |
|-------------------------------|---|--|--|---|--|--|
| Yellow Metal | scalar | *Visual | NONE | LIGHT | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | | | |
| Emulsified Water | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | history1 | history2 |
| | | | | | | |
| SAMPLE IMAGE | -5 | method | limit/base | current | history1 | history2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |
| GRAPHS | | | | | | |
| | | | | | | |
| Copper copper lead 4 | als | | Jun 13/24 | | | |
| Viscosity @ 40°C | | | Jun13/24 | Acid Number | | |
| | | | (^B)H | Base | | |
| Rase | | | ο.e | 10 | | |
| 9 27 27 24 140 | | | <u>ق</u> 0.3 تق | 30 - | | |
| 100 | | | 40.1 | | | |
| 130 Abnormal | | | Acid 1 | 10 | | |
| 120 | | | Jun13/24 | Jun 13/24 | | |
| Jun13/24 | | | | | | |
| | Debris Sand/Dirt Appearance Odor Emulsified Water Free Water FLUID PROPER Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys | Debris scalar Sand/Dirt scalar Appearance scalar Odor scalar Emulsified Water scalar Free Water scalar Free Water scalar FLUID PROPERTIES Visc @ 40°C cSt SAMPLE IMAGES Color Bottom GRAPHS Ferrous Alloys Ferrous Alloys Visce Und Copper Non-ferrous Metals | Debris scalar *Visual Sand/Dirt scalar *Visual Appearance scalar *Visual Emulsified Water scalar *Visual Emulsified Water scalar *Visual Free Water scalar *Visual FLUID PROPERTIES method Visc @ 40°C cSt ASTM D445 SAMPLE IMAGES method Color Bottom GRAPHS Ferrous Alloys Viscosity @ 40°C Viscosity @ 40°C Viscosity @ 40°C | Debris scalar *Visual NONE Sand/Dirt scalar *Visual NORML Appearance scalar *Visual NORML Emulsified Water scalar *Visual >0.2 Free Water scalar *Visual >0.2 Free Water scalar *Visual FLUID PROPERTIES method limit/base Visc @ 40°C cSt ASTM D445 152.9 SAMPLE IMAGES method limit/base Color Color GRAPHS Ferrous Alloys ferrous Alloys 0 0 0 0 0 0 0 0 0 0 0 0 0 | Debris scalar *Visual NONE MODER Sand/Dirt scalar *Visual NONE NONE Appearance scalar *Visual NORML NORML Odor scalar *Visual NORML NORML Emulsified Water scalar *Visual >0.2 NEG Free Water scalar *Visual >0.2 NEG SAMPLE IMAGES method limit/base current Visc @ 40°C cSt ASTM D445 152.9 139 SAMPLE IMAGES method limit/base current Color GRAPHS Ferrous Alloys 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | Debris scalar *Visual NONE MODER Sand/Dirt scalar Visual NONE NONE Appearance scalar Visual NORML NORML Codor scalar Visual NORML NORML Emulsified Water scalar Visual >0.2 NEG Free Water scalar Visual NORML NORML Emulsified Water scalar Visual NORML NORML Emulsified Water scalar Visual NORML NORML Emulsified Visual NOR |

Report Id: UCCORROC [WUSCAR] 06210085 (Generated: 06/22/2024 19:11:13) Rev: 1

Contact/Location: Bill Cox - UCCORROC

history2

history1