

## **OIL ANALYSIS REPORT**

### Area ULTRA COOLANT [126679] INGERSOLL RAND CBV362153 - PLUG POWER

Component Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

SAMPLE INFORM	<b>/IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06210219		
Sample Date		Client Info		04 Jun 2024		
Machine Age	hrs	Client Info		39450		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	2		
Tin	ppm	ASTM D5185m	>15	1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	2		
Barium	ppm	ASTM D5185m	500	755		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	0	0		
Calcium	ppm	ASTM D5185m	0	0		
Phosphorus	ppm	ASTM D5185m	20	0		
Zinc	ppm	ASTM D5185m	0	14		
Sulfur	ppm	ASTM D5185m	200	434		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m		45		
Potassium	ppm	ASTM D5185m	>20	6		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.33		



40 Jun4/24

# **OIL ANALYSIS REPORT**



	VISUAL		method	limit/base	current	history1	history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Jun4,24	Appearance	scalar	*Visual	NORML	NORML			
٦ ٦	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	IES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445	49.4	51.9			
-	SAMPLE IMAGES	6	method	limit/base	current	history1	history2	
Jun4,24	Color					no image	no image	
	Bottom					no image	no image	
	2			Jun4/24				
	Non-ferrous Metal	S						
	2							
	Jun4/24			Jun4/24				
	Viscosity @ 40°C				Acid Number			
	<sup>70</sup> <sub>65</sub> Severe			⊋ <sup>2.50</sup>	Severe			
	Abnormal			호 2.00 및				
	0 00 00000000000000000000000000000000			(5,2,50 (6,1,2,0) (6,1,0) (6,1,0) (6,1,0) (6,1,0) (6,1,0) (7,1	Abnormal			
	45 Severe							
	14/24							
Laboratory	40 <td< th=""></td<>							

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRSID [WUSCAR] 06210219 (Generated: 06/17/2024 17:40:03) Rev: 1

Contact/Location: ANGIE ROSENBECK - UCAIRSID

F: (937)492-3147