

OIL ANALYSIS REPORT

Sample Rating Trend



Area CS 46 [O-SP3185828] KAESER 1107 - CLOROX Component

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06210234	UCH05508630	
Sample Date		Client Info		30 May 2024	22 Mar 2022	
Machine Age	hrs	Client Info		60151	49633	
Oil Age	hrs	Client Info		20518	0	
Oil Changed		Client Info		Changed	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1	0	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	3	6	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1.5	<1	0	
Barium	ppm	ASTM D5185m	0	0	0	
Molybdenum	ppm	ASTM D5185m	0	<1	0	
Manganese	ppm	ASTM D5185m	0.3	<1	0	
Magnesium	ppm	ASTM D5185m	0	0	<1	
Calcium	ppm	ASTM D5185m	0	0	0	
Phosphorus	ppm	ASTM D5185m	406	108	1	
Zinc	ppm	ASTM D5185m	0	0	35	
Sulfur	ppm	ASTM D5185m	1283	4069	16051	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	5	<1	
Sodium	ppm	ASTM D5185m		1	0	
Potassium	ppm	ASTM D5185m	>20	3	1	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	0.49	0.47	



OIL ANALYSIS REPORT

VISUAL



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	LIGHT	VLITE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
May30/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
May	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	47.9	48.2	48.6	
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
May30.24 +	Color						no image
	Bottom						no image
	GRAPHS						
	Ferrous Alloys						
	10 iron 1						
	6						
	2						
	0						
	Mar22/22			May30/24			
	Mar			May			
	Non-ferrous Meta	als					
	10 copper						
	6						
	- 4						
	2						
	2						
	2			/30/24			
	2			May30/24			
	Viscosity @ 40°C				Acid Number		
	2						
	Viscosity @ 40°C			0.50 Ho 40	Base		
	Viscosity @ 40°C			0.50 Ho 40	Base		
	Viscosity @ 40°C			0.50 Ho 40	Base		
	Viscosity @ 40°C			0.50 Ho 40	Base		
	Viscosity @ 40°C			(0.50) (0.40) (0.30) (0.10) (0	Base		
	Viscosity @ 40°C			0.50 Ho 40	Base		

Report Id: UCCISHAY [WUSCAR] 06210234 (Generated: 06/17/2024 17:39:30) Rev: 1

Contact/Location: JOHN FINCH - UCCISHAY