




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
FREIGHTLINER FL70 DRW-1
 Component
Diesel Engine
 Fluid
 DIESEL ENGINE OIL SAE 40 (18 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0632533	WCM1394290	---
Sample Date	Client Info		14 May 2024	30 Apr 2023	---
Machine Age	hrs	Client Info	200	0	---
Oil Age	hrs	Client Info	200	300	---
Oil Changed	Client Info		Changed	N/A	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	31	15	---
Chromium	ppm	ASTM D5185m >5	2	<1	---
Nickel	ppm	ASTM D5185m >2	<1	0	---
Titanium	ppm	ASTM D5185m	0	0	---
Silver	ppm	ASTM D5185m >3	0	<1	---
Aluminum	ppm	ASTM D5185m >30	14	3	---
Lead	ppm	ASTM D5185m >30	2	0	---
Copper	ppm	ASTM D5185m >150	13	<1	---
Tin	ppm	ASTM D5185m >5	2	0	---
Vanadium	ppm	ASTM D5185m	0	<1	---
Cadmium	ppm	ASTM D5185m	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	117	69	---
Barium	ppm	ASTM D5185m 10	0	0	---
Molybdenum	ppm	ASTM D5185m 100	24	4	---
Manganese	ppm	ASTM D5185m	1	<1	---
Magnesium	ppm	ASTM D5185m 450	110	19	---
Calcium	ppm	ASTM D5185m 3000	1930	2584	---
Phosphorus	ppm	ASTM D5185m 1150	949	1127	---
Zinc	ppm	ASTM D5185m 1350	1129	1419	---
Sulfur	ppm	ASTM D5185m 4250	3727	4477	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	45	4	---
Sodium	ppm	ASTM D5185m >216	12	2	---
Potassium	ppm	ASTM D5185m >20	6	<1	---

INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.8	0.4	---
Nitration	Abs/cm	*ASTM D7624 >20	9.5	9.9	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.9	18.1	---


FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	14.6	15.0	---
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	7.3	6.6	---




OIL ANALYSIS REPORT


FT-IR (Direct Trend)



Base Number




Viscosity @ 100°C



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.3	13.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0632533 **Received** : 17 Jun 2024
Lab Number : 06211282 **Tested** : 18 Jun 2024
Unique Number : 11084146 **Diagnosed** : 18 Jun 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

D&R WATTS GRADING
 501 ROBIN CT
 ARCHDALE, NC
 US 27263
 Contact: DANIEL WATTS
 d_rwattsgading@yahoo.com
 T: (336)362-0290
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)