

# **OIL ANALYSIS REPORT**

Sample Rating Trend

# ISO

# Area **[UNITED RENTALS 22] JCB 427 3079425** Component Hydraulic System

Fluid Fluid JCB 46 (64 GAL)

### DIAGNOSIS

### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

## Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of particulates present in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

SAMPLE INFURI		method	iimii/base	current	nistory i	nistory2
Sample Number		Client Info		JCB005684		
Sample Date		Client Info		16 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	2		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>10	1		
Copper	ppm	ASTM D5185m	>75	2		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	mag	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		۔ د1		
Claiman	PPIII			~		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		34		
Phosphorus	ppm	ASTM D5185m		305		
Zinc	ppm	ASTM D5185m		409		
Sulfur	ppm	ASTM D5185m		772		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon				_		
	ppm	ASTM DS185m	>20	2		
Sodium	ppm ppm	ASTM D5185m ASTM D5185m	>20	2		
Sodium Potassium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>20 >20	2 0 <1		
Sodium Potassium FLUID CLEANLIN	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m method	>20 >20 limit/base	2 0 <1 current	  history1	  history2
Sodium Potassium FLUID CLEANLIN Particles >4µm	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647	>20 >20 limit/base >5000	2 0 <1 current 7322	  history1	  history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300	2 0 <1 current 7322 2058	  history1 	  history2 
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160	2 0 <1 0 0 2058 87	  history1 	 history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160 >40	2 0 <1 0 0 207 322 2058 87 15	  history1  	 history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm	ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m Method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160 >40 >10	2 0 <1 0 2058 87 15 0	  history1    	 history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm	ppm ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 >20 limit/base >5000 >1300 >160 >40 >10 >3	2 0 <1 0 7322 2058 87 15 0 0	 history1    	 history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness	ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ISO 4406 (c)	>20 >20 limit/base >5000 >1300 >160 >40 >10 >3 >3 >19/17/14	2 0 <1 current 7322 2058 87 15 0 0 0 20/18/14	 history1      	 history2
Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness	ppm ppm IESS	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ISO 4406 (c) method	>20 >20 limit/base >5000 >1300 >160 >40 >10 >3 >19/17/14 limit/base	2 0 <1 201 2058 87 15 0 0 20/18/14 20/18/14	  history1       history1	 history2      history2

Report Id: BRITAM [WUSCAR] 06211543 (Generated: 06/19/2024 08:18:03) Rev: 1

Contact/Location: CHRIS RYALS - BRITAM Page 1 of 2



# **OIL ANALYSIS REPORT**



Contact/Location: CHRIS RYALS - BRITAM

T:

F:

0SI

:1999 Cle

14

4406