

OIL ANALYSIS REPORT

Machine Id TRANE WSU BIO SCIENCE (S/N L90D00989)

Component Refrigeration Compressor Fluid

TRANE 0022 (9 GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0758364	WC0618823	WC0507684
Sample Date		Client Info		10 May 2024	28 Jan 2022	06 Nov 2020
Machine Age	hrs	Client Info		96132	88002	84150
Oil Age	hrs	Client Info		96132	88002	0
Oil Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL
		mothod	limit/baco	ourropt	history1	history?
WEAR METALS		methou	iiiiii/base	Current	instory i	
Iron	ppm	ASTM D5185m	>8	<1	<1	<1
Chromium	ppm	ASTM D5185m	>2	0	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>3	0	0	0
Lead	ppm	ASTM D5185m	>2	0	0	0
Copper	ppm	ASTM D5185m	>8	<1	0	0
Tin	ppm	ASTM D5185m	>4	0	<1	<1
Antimony	ppm	ASTM D5185m			0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		6	6	2
Zinc	ppm	ASTM D5185m		<1	0	0
Sulfur	ppm	ASTM D5185m		1	13	14
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	4	4	0
Sodium	ppm	ASTM D5185m		2	0	0
Potassium	ppm	ASTM D5185m	>20	0	0	<1
Water	%	ASTM D6304	>0.005	0.002	0.003	0.002
ppm Water	ppm	ASTM D6304	>50	21	36.3	15.2
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	2463		
Particles >6µm		ASTM D7647	>2500	364		
Particles >14µm		ASTM D7647	>320	4		
Particles >21µm		ASTM D7647	>80	1		
Particles >38µm		ASTM D7647	>20	0		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	18/16/9		
FLUID DEGRADA		method	limit/base	current	history1	history2

Acid Number (AN) mg KOH/g ASTM D974 0.038 0.014

Report Id: MCQLIV [WUSCAR] 06211729 (Generated: 06/22/2024 02:41:45) Rev: 1

0.013 Submitted By: RICK VANOVERBEKE



OIL ANALYSIS REPORT











Bottom



* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MCQLIV [WUSCAR] 06211729 (Generated: 06/22/2024 02:41:45) Rev: 1

Submitted By: RICK VANOVERBEKE

Page 2 of 2

T: (248)364-4532

F: (248)364-4530