

OIL ANALYSIS REPORT

Vanadium

Area **NOT** GIVEN **KAESER 1393 - EVONIK**

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

method				
	May20	24		
			N	I C

Sample Rating Trend

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0001646		
Sample Date		Client Info		29 May 2024		
Machine Age	hrs	Client Info		61175		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
WEAR METALS	ppm	method ASTM D5185m	limit/base	current <1	history1	history2
	ppm ppm				history1 	history2
Iron		ASTM D5185m	>50	<1		
Iron Chromium	ppm	ASTM D5185m ASTM D5185m	>50 >10	<1 0		
Iron Chromium Nickel	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>50 >10 >3	<1 0 0		
Iron Chromium Nickel Titanium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >10 >3 >3	<1 0 0 <1		
Iron Chromium Nickel Titanium Silver	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >10 >3 >3 >2	<1 0 0 <1 0		
Iron Chromium Nickel Titanium Silver Aluminum	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	>50 >10 >3 >3 >2 >10 >10	<1 0 0 <1 0 0		

Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		213		
Zinc	ppm	ASTM D5185m		<1		
Sulfur	ppm	ASTM D5185m		780		
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		

Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m	1			
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2

Acid Number (AN) mg KOH/g ASTM D8045 0.74




ppm ASTM D5185m





OIL ANALYSIS REPORT



	VISUAL		method				history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
May29/24	Appearance	scalar	*Visual	NORML	NORML		
Mar	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.05	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPERT	IES	method	limit/base	e current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		55.3		
	SAMPLE IMAGES	;	method	limit/base	e current	history1	history2
May29/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Metals	5		May29/24			
	Viscosity @ 40°C			Acid Number (mg KOH/g)	.00		924
Laboratory Sample No. Lab Number Unique Number Test Package o discuss this sample report, Denotes test methods that	: 11084689 : IND 2 contact Customer Servid are outside of the ISO 17	Recei Teste Diagn ce at 1-8 7025 sco	ived : 17 d : 18 iosed : 19 200-237-1369 ipe of accrea	7 Jun 2024 8 Jun 2024 Jun 2024 - Do 9. Jitation.		36 MOUN MORC Contact: Se	RE DYNAMICS FAIN VIEW RD GANTOWN, PA US 19543 ervice Manager T: F:

Contact/Location: Service Manager - UCFLUMOR