

# **OIL ANALYSIS REPORT**

Sample Rating Trend





**MINING** ME-301 VOLVO L350F 1961 Component Rear Left Final Drive

# Fluid SHELL Spirax S4 CX 30 (--- GAL)

#### Recommendation

Resample at the next service interval to monitor.

Area

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0928249		
Sample Date		Client Info		11 Jun 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	J	method	limit/base	current	history1	history2
Water	v	WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>1000	27		
Chromium	ppm	ASTM D5185m	>10	1		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>25	- <1		
Copper	ppm	ASTM D5185m	>30	7		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m	210	0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES	1-1-	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	mmbddoc	126		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		۰ <1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium		ASTM D5185m		14		
Calcium	ppm ppm	ASTM D5185m		3806		
Phosphorus		ASTM D5185m		1161		
Zinc	ppm	ASTM D5185m		1585		
-	ppm			3906		
Sulfur	ppm	ASTM D5185m		3900		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>30	11		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	1		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
	scalar scalar	*Visual *Visual	NONE	NONE MODER		
Precipitate						
Precipitate Silt	scalar	*Visual	NONE	MODER		
Precipitate Silt Debris	scalar scalar	*Visual *Visual	NONE NONE	MODER NONE		
Precipitate Silt Debris Sand/Dirt	scalar scalar scalar	*Visual *Visual *Visual	NONE NONE NONE	MODER NONE NONE		
Precipitate Silt Debris Sand/Dirt Appearance	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NONE NORML	MODER NONE NONE NORML		
Precipitate Silt Debris Sand/Dirt Appearance Odor	scalar scalar scalar scalar scalar	*Visual *Visual *Visual *Visual *Visual	NONE NONE NORML NORML	MODER NONE NONE NORML NORML		



# **OIL ANALYSIS REPORT**



FLUID PROPERTIES	method limit/base	current	history1	history2
Visc @ 40°C cSt	ASTM D445 93.9	42.4		
SAMPLE IMAGES	method limit/base	current	history1	history2
Color		no image	no image	no image
Dettern				/
Bottom		no image	no image	no image
GRAPHS				
Ferrous Alloys				
30				
25 - second chromium				
20				
<u>ة</u> 15 -				
10-				
5 -				
0				
Jun11/24	Jun11/24			
Non-ferrous Metals				
9 - copper ]				
8 - enseense tin				
7				
E 5-				
4 -				
3				
1-				
0	24			
Jun 1 1/24	Jun 11/24			
Viscosity @ 40°C				
160 Abnormal				
140 -				
120 -				
(3 0) 0 0 100 - Base				
80 Abnormal				
60 -				
40				
Jun 11/24	Jun 11/24			
un r	un r			
: WearCheck USA - 501 Madis : WC0928249 Rece	on Ave., Cary, NC 27513 e <b>ived</b> : 17 Jun 2024			<b>ORTAGE - 0</b> 82 US HWY
: 06212139 Test				DEEVILLE,
	nosed : 19 Jun 2024 - Do	n Baldridge		US 539
: CONST (Additional Tests: PC contact Customer Service at 1-	2) 200 227 1260		Conta sean.lyons@	ict: Sean Lyo

Certificate 12367 Test Package : CONST (Additional Tests: PQ) To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (507)514-2204

Page 2 of 2

F: