

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

7112390 (S/N 1042)

Component Compressor Fluid KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA017686		
Sample Date		Client Info		01 May 2024		
Machine Age	hrs	Client Info		16767		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>3	0		
Titanium	ppm	ASTM D5185m	>3	<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	<1		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m		3		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m	- 10	<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0		
Barium	ppm	ASTM D5185m	90	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	U	۰ <1		
Magnesium	ppm	ASTM D5185m	100	3		
Calcium	ppm	ASTM D5185m	0	0		
Phosphorus		ASTM D5185m	0	339		
Zinc	ppm	ASTM D5185m	0	36		
Sulfur	ppm	ASTM D5185m	23500	4040		
	ppm					
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		7		
Potassium	ppm	ASTM D5185m	>20	<1		
Water	%	ASTM D6304		0.009		
ppm Water	ppm	ASTM D6304	>500	97		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		7005		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14µm		ASTM D7647	>80	127		
Particles >21µm		ASTM D7647	>20	11		
		ASTM D7647	>4	0		
Particles >38µm				•		
Particles >38µm Particles >71µm		ASTM D7647	>3	0		
		ASTM D7647 ISO 4406 (c)	>3 >/17/13	0 <u> </u> 20/19/14		
Particles >71µm	TION			-		



Built for a lifetime." 🔺 Particle Trend

Water (KF)

Sev 10000

4µm

μm 14µm

8k 71

Ê Gk

) salojued 4k 31 2k 11 Ok May1/24

12000

800 Water (ppm) 6000 4000

2000

1.20

(B/H0.9 KOH/d) E0.72 a u u 0.48 Pio 0.24 0.00 VC. U av

12000

10000 Sever

> 60 Se 55

() 50 () 50 15 45 Base Abnormal 40 Ser

35 74 Mav1

B


/Jav1

Acid Number

Water (KF)

Abnormal 0 Mav1/2/

Viscosity @ 40°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water Free Water	scalar	*Visual	>0.05	NEG NEG		
	scalar	*Visual		NEG		
FLUID PROPER	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	48.6		
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color					no image	no image
				Contra BRI'C		
Bottom					no image	no image
GRAPHS						
Ferrous Alloys			491,520	Particle Count		T ²⁶
8 - iron chromium			122,880			-24
E 6 A						
2			30,720	-		-22
0			7,680			-20 3
May1/24			(per 1 ml) (per 1 ml)			-18 5
			M icles (p		N	
Non-ferrous Meta	115		9480 480			16 9
10			5			
8 - copper			Jo nage 120	-	1	-14
8 - copper			+5/1/keW (m 1.32(120) 120) 120 120 120 120 120 120 120 120 120 120			-10 - -18 - -16 - -16 - -14 - -14 - -12 -
8 - copper lead			30) -		
8 - copper			30			+14 g +12 +10
B copper lead 4 2 0			30	3 Sizver mal		
udd copper ead 0 +2//kew			30	3 Sizver mal	1411 27111	-10
viscosity @ 40°C			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	
udd copper ead 0 +2//kew			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	-10
Viscosity @ 40°C			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	-10
Viscosity @ 40°C			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	-10
Viscosity @ 40°C			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	-10
Viscosity @ 40°C			30	2 4 4 4 4 4 4 4 4 4 4 4 4 4	14μ 21μ	-10

- To discuss this sample report, contact Customer Service at 1-800-237-1369.
- * Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: Service Manager - NATSANTX

T:

F: