


OIL ANALYSIS REPORT



OKLAHOMA/102/EG - BACKHOE LOADER 53.513L [OKLAHOMA^102^EG - BACKHOE LOADER]

Diesel Engine

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: 5726 hours)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0925207	WC0864309	WC0819949
Sample Date		Client Info		10 Jun 2024	05 Feb 2024	09 Sep 2023
Machine Age	hrs	Client Info		6726	5664	5215
Oil Age	hrs	Client Info		5700	5664	5215
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	l	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	39	29	35
Chromium	ppm	ASTM D5185m	>20	2	2	2
Nickel	ppm	ASTM D5185m	>2	<1	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	13	12	12
Lead	ppm	ASTM D5185m	>40	0	0	<1
Copper	ppm		>330	8	5	6
Tin	ppm	ASTM D5185m	>15	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	<1	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	53	55	52
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	41	41	36
Manganese	ppm	ASTM D5185m		1	0	<1
Magnesium	ppm	ASTM D5185m	0	523	488	493
Calcium	ppm	ASTM D5185m		1728	1631	2051
Phosphorus	ppm	ASTM D5185m		814	810	835
Zinc	ppm	ASTM D5185m		955	920	1019
Sulfur	ppm	ASTM D5185m		3013	2641	3592
CONTAMINANTS	ppm	ASTM D5185m method	limit/base			3592 history2
	ppm			3013	2641	
CONTAMINANTS	ppm	method		3013 current	2641 history1	history2
CONTAMINANTS Silicon		method ASTM D5185m	>25	3013 current 23	2641 history1 20	history2 22
CONTAMINANTS Silicon Sodium	ppm ppm	method ASTM D5185m ASTM D5185m	>25	3013 current 23 4	2641 history1 20 1	history2 22 3
CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m method	>25 >20 limit/base	3013 current 23 4 4 current	2641 history1 20 1 3 history1	history2 22 3 2 history2
CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844	>25 >20 limit/base >3	3013	2641 history1 20 1 3 history1 0.2	history2 22 3 2 history2 0.1
CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m method	>25 >20 limit/base	3013 current 23 4 4 current	2641 history1 20 1 3 history1	history2 22 3 2 history2
CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm % Abs/cm Abs/.1mm	method ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	>25 >20 limit/base >3 >20	3013	2641 history1 20 1 3 history1 0.2 7.9	history2 22 3 2 history2 0.1 6.6
CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm % Abs/cm Abs/.1mm	method ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415 method	>25 >20 limit/base >3 >20 >30 limit/base	3013	2641 history1 20 1 3 history1 0.2 7.9 21.4 history1	history2 22 3 2 history2 0.1 6.6 21.4 history2
CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % Abs/cm Abs/.1mm	method ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415	>25 >20 limit/base >3 >20 >30 limit/base >25	3013	2641 history1 20 1 3 history1 0.2 7.9 21.4	history2 22 3 2 history2 0.1 6.6 21.4



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPER	TIES	method				history2
Visc @ 100°C	cSt	ASTM D445	14	13.2	13.1	13.3

GRAPHS













Certificate 12367

Laboratory Sample No.

: WC0925207 Lab Number : 06212733 Unique Number : 11085597

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 17 Jun 2024 Received

Tested Diagnosed Test Package : CONST (Additional Tests: TBN)

: 19 Jun 2024 : 19 Jun 2024 - Angela Borella

SHERWOOD CONSTRUCTION CO INC 3219 WEST MAY ST WICHITA, KS US 67213

Contact: DOUG KING doug.king@sherwood.net

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

F: x: Submitted By: LOUIS BRESHEARS

T: (316)617-3161