

# **OIL ANALYSIS REPORT**

Sample Rating Trend

## NORMAL

## Area AEON 2000/South end INGERSOLL RAND 00009364 - TERMINAL RAILROAD (S/N VL1992U15262) Component

Air Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		JHF0000427		
Sample Date		Client Info		07 Jun 2024		
Machine Age	hrs	Client Info		54154		
Oil Age	hrs	Client Info		2389		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.6	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>4	0		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m	- 1	0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>40	0		
Tin	ppm	ASTM D5185m	>5	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		1		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		36		
Phosphorus	ppm	ASTM D5185m		225		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		447		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		14		
Potassium	ppm	ASTM D5185m	>20	3		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.3	0.29		



52 Jun7/24

# **OIL ANALYSIS REPORT**



	VISUAL		method				history2	
	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Jun7/24	Appearance	scalar	*Visual	NORML	NORML			
٦ ٢	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.6	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT	IES	method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445	60.0	57.0			
	SAMPLE IMAGES	3	method	limit/base	current	history1	history2	
+2/LmJ	Color					no image	no image	
	Bottom					no image	no image	
	mqq			Jun7/24				
	Non-ferrous Metal	S		Jun7/24				
	⊰ Viscosity @ 40°C			٦n	Acid Number			
	70 65 65 65 65 65 65 65 65 65 65			(0.40 (0.00 0.30 (0.10 0.20 (0.10 0.10 (0.10 0.10) (0.10 0.10) (0.10)	Base			
	55 <b>Abnormal</b> 50 + + + + + - + + - + + - + + - + + - + + - + + - + + - + + - + + - + + - + + - + + - +			Acid N Acid N 0000	Jun7/24			
Laboratory Sample No. Lab Number Unique Number	: WearCheck USA - 50 : JHF0000427 : <mark>06214793</mark>	1 Madiso Recei Teste Diagr	ved : 19 d : 20	, NC 27513 ) Jun 2024 ) Jun 2024	NC 27513 JOHN HENRY FOSTER COMPAN un 2024 4700 LEBOURGET STREE			

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCJOHSAI [WUSCAR] 06214793 (Generated: 06/21/2024 14:06:49) Rev: 1

Submitted By: RACHEL VON HATTEN

Page 2 of 2

F: (314)874-0965